



TECHNICAL DATA SHEET

1K BUMPER TEXTURE BLACK

PRODUCT DESCRIPTION

1K Bumper Texture Black is a flexible black satin textured finish specifically designed for use on bumper bars.

PRODUCT AND ADDITIVES

- Concept 1K Bumper Texture Black
- Concept Multi-Thinner




SUITABLE SUBSTRATES

- Sound existing finishes.
- New bumper bars primed with Concept Plastic Primer.

MIXING RATIO




- Up to 30% reduction with Concept Multi-Thinner may be required.

SPRAY GUN AND PRESSURE

SPRAY GUN & PRESSURE:	<ul style="list-style-type: none">• 2.0mm tip with a suction feed gun• Pressure is 350 – 400 kPa. (The same condition applies for gravity feed)	
--------------------------	--	---

APPLICATION

- Except for surfaces primed with Concept Plastic Primer, all other surfaces must be thoroughly sanded and cleaned with Concept Wax & Grease Remover prior to application.
- Apply two to three even coats.

SPRAYING VISCOSITY:	<ul style="list-style-type: none"> • 18 – 20 seconds B4 cup at 25°C. 	 <p style="font-size: small; margin: 0;">18-20 SECONDS</p>
FLASH-OFF TIME:	<ul style="list-style-type: none"> • 5 minutes between coats at 25°C. 	
DRYING:	<ul style="list-style-type: none"> • 2 – 3 hours at 25°C for a Dry Film Thickness of 40 – 50 Micron. 	

TECHNICAL INFORMATION

COLOUR:	Black
COVERAGE:	3 m ² /L @ 50 Micron Dry Film Thickness.
VOC:	696 g/L
GLOSS:	Satin
PACKAGING:	1LT, 4LT, 20LT
ITEM CODE:	A03D/TXTB
SHELF LIFE:	12 Months

The above information is reliable and accurate to the best of our knowledge at the time of preparation. Any recommendations or suggestions made are without warranty or guarantee. Users assume all responsibility since the conditions of use are beyond our control.

REVISED: 14 May 2013

REPLACES ISSUE: 21 September 2012

1K Bumper Texture Black

Page 2 of 2