

CONCEPT **PAINTS**®

TECHNICAL DATA SHEET

760 1K METAL CLEAR

PRODUCT DESCRIPTION

This high gloss single pack clear coat has been designed to be used directly over aluminium, stainless steel and metal surfaces for protection. It has excellent flow, producing a high gloss film with very good water resistance.

PRODUCT AND ADDITIVES

- Concept 760 1K Metal Clear


SUITABLE SUBSTRATES

- Aluminium, stainless steel, alloy or metal.

MIXING RATIO




- Supplied ready for use. No thinning required.

SPRAY GUN AND PRESSURE

SPRAY GUN & PRESSURE:	<ul style="list-style-type: none">• 1.2 - 1.5 mm through a suction feed.• Pressure is 350 – 450 kPa (gravity feed will apply)	
--------------------------	--	---

APPLICATION

- All surfaces must be thoroughly cleaned with Concept Wax & Grease Remover prior to application.
- Apply three even coats

SPRAYING VISCOSITY:	<ul style="list-style-type: none"> • 18 – 22 seconds B4 cup at 25°C. 	 18 - 22 SECONDS
FLASH-OFF TIME:	<ul style="list-style-type: none"> • 5 – 10 minutes between coats at 25°C. 	
DRYING:	60 – 90 minutes at 25°C for a Dry Film Thickness of 40 – 50 Micron.	

TECHNICAL INFORMATION

COLOUR:	Clear
COVERAGE:	3 m ² /L @ 50 Micron Dry Film Thickness.
VOC:	740 g/L
PACKAGING:	4LT
ITEM CODE:	A07C/760/4
SHELF LIFE:	12 Months

The above information is reliable and accurate to the best of our knowledge at the time of preparation. Any recommendations or suggestions made are without warranty or guarantee. Users assume all responsibility since the conditions of use are beyond our control.

REVISED: 04 June 2015

REPLACES ISSUE: