



TECHNICAL DATA SHEET

ACRYLIC TOPCOAT CLEAR (SPRAYPAK)

PRODUCT DESCRIPTION

Concept's Acrylic Topcoat Clear Spraypak is a high quality clear coat product, suitable for all metallic based and acrylic automotive paints. The superior performance of the Acrylic Topcoat Clear produces a tough flexible high gloss finish with exceptional durability and adhesion, better suited for the Australian conditions.

PRODUCT AND ADDITIVES

- Concept Acrylic Topcoat Clear Spraypak

SUITABLE SUBSTRATES

- Concept No Mix Basecoat and Acrylic paint systems.

SUBSTRATE PREPARATION

- Ensure that all surfaces are clean and free from any contamination prior to application.
- Mask off surrounding areas to avoid overspray.

MIXING

- Ready for Use
- Invert and shake the can thoroughly, until the agitation ball can be heard (two to three minutes). Continue to shake the can during application.

APPLICATION

- Spray in an even overlapping pattern from a distance of approximately 25 centimetres.
- Apply two to three even coats to gradually increase film thickness.
- Avoid heavy coats which may run.
- Allow 5 minutes flash off between coats.

Drying @ 25°C:	40 – 60 Minutes
-----------------------	-----------------

- Optional: Sand with P1200 abrasive prior to buffing.

AFTER USE

- Turn the can upside down and spray until the jet clears.
- Any over spray maybe cleaned up with Mineral Turps.

TECHNICAL INFORMATION

COLOUR:	Clear
COVERAGE:	3 m ² /400g @ 25 Micron Dry Film Thickness.
PACKAGING:	400g
ITEM CODE:	A07C/1KCLR/400G
SHELF LIFE:	12 Months

The above information is reliable and accurate to the best of our knowledge at the time of preparation. Any recommendations or suggestions made are without warranty or guarantee. Users assume all responsibility since the conditions of use are beyond our control.

REVISED: 16 September 2015

REPLACES ISSUE: 23 April 2015