



TECHNICAL DATA SHEET

CONCRETE PAINT CONVERTER

PRODUCT DESCRIPTION

This product is an additive used with Concept Unicryl 3000 colours to convert it into an acrylic based concrete coating for most concrete surfaces. It improves hardness, adhesion and wear resistance in high traffic areas.

PRODUCT AND ADDITIVES

- Concept Concrete Paint Converter
- Concept Unicryl 3000



SUITABLE SUBSTRATES


- Most unpainted concrete surfaces.
- Sound existing surfaces.

MIXING RATIO

- 1 Part Concept Unicryl 3000 Colour by volume.
- 40% Concept Concrete Paint Converter by volume.

APPLICATION

- All surfaces must be clean, dry and free from oil and grease.
- Steel trowelled concrete surfaces must be acid washed prior to application.
- Prepainted surfaces in sound condition must be thoroughly sanded and cleaned with Concept Wax & Grease Remover prior to application. Poor surfaces should be removed using either sandblasting or high pressure water.
- Apply two even coats with either a brush or roller.

<p>DRYING:</p>	<ul style="list-style-type: none"> • 40 – 60 minutes at 25°C for a Dry Film Thickness of 40 – 50 Micron. 	
----------------	---	---

TECHNICAL INFORMATION

COLOUR:	Clear Thin Liquid
COVERAGE:	5 m ² /L @ 50 Micron Dry Film Thickness.
VOC:	839 g/L
PACKAGING:	4LT, 20LT
ITEM CODE:	A08/CONVERTER
SHELF LIFE:	12 Months

The above information is reliable and accurate to the best of our knowledge at the time of preparation. Any recommendations or suggestions made are without warranty or guarantee. Users assume all responsibility since the conditions of use are beyond our control.

REVISED: 14 June 2013

REPLACES ISSUE: 21 March 2005