



TECHNICAL DATA SHEET

GMH BLACK **(SPRAYPAK)**

PRODUCT DESCRIPTION

This is a fast drying nitrocellulose based lacquer specifically designed for automotive underbody detailing. It is also suitable as a guide coat prior to sanding of primers.

PRODUCT AND ADDITIVES

- Concept GMH Black Spraypak

SUITABLE SUBSTRATES

- Previously painted Underbodies/Chassis in sound condition.
- Guide coat on Concept Primer range.

SUBSTRATE PREPARATION

- Ensure that all surfaces are clean and free from any contamination prior to application.
- Mask off surrounding areas to avoid overspray.

MIXING

- Ready for Use
- Invert and shake the can thoroughly, until the agitation ball can be heard (two to three minutes). Continue to shake the can during application.

APPLICATION

- Spray in an even overlapping pattern from a distance of approximately 25 centimetres.
- Apply two to three even coats to gradually increase film thickness.
- Avoid heavy coats which may run.
- Allow 5 minutes flash off between coats.

Drying @ 25°C:	20 – 30 Minutes
-----------------------	-----------------

AFTER USE

- Turn the can upside down and spray until the jet clears.
- Any over spray maybe cleaned up with Mineral Turps.

TECHNICAL INFORMATION

COLOUR:	Black
COVERAGE:	3 m ² /400g @ 25 Micron Dry Film Thickness.
PACKAGING:	400g
ITEM CODE:	
SHELF LIFE:	12 Months

The above information is reliable and accurate to the best of our knowledge at the time of preparation. Any recommendations or suggestions made are without warranty or guarantee. Users assume all responsibility since the conditions of use are beyond our control.

REVISED: 22 May 2015

REPLACES ISSUE: 27 March 2015