



TECHNICAL DATA SHEET

HI-TEK (BODY FILLER)

PRODUCT DESCRIPTION

Concept's Hi-Tek Body Filler is manufactured from a blend of high grade resins to maximise its performance. It is ideally suited for filling dents, cracks and rust holes in most metals.

PRODUCT AND ADDITIVES

- Concept Hi-Tek (Body Filler)
- Concept Benzoyl Peroxide Hardener (50% w/w)



SUITABLE SUBSTRATES



- Most metal surfaces.
- Glass reinforced polyester.

MIXING RATIO

- 40 – 50 parts of Concept Hi-Tek (Body Filler).
- 1 part Concept Benzoyl Peroxide Hardener (50% w/w).
- Thoroughly mix until an even colour is obtained.

APPLICATION

- All surfaces must be thoroughly sanded prior to application.
- Apply putty to surface with firm pressure, do not apply heavy coats. Apply thin layers working to a smooth surface.

DRYING:	<ul style="list-style-type: none">• 20 – 30 minutes at 25°C.	
SANDING:	<ul style="list-style-type: none">• Use 36/40 grade paper and finish off with 100/200 grit fre-cut. Sand thoroughly before applying finish coat.	

TECHNICAL INFORMATION

COLOUR:	Off White
VOC:	Filler: 162 g/L, Hardener: 0 g/L
PACKAGING:	500gms, 1KG, 2.5KG, 4.5KG Hardener: 75gms, 100gms
ITEM CODE:	A03E/HITEK (Hardener: A03E/BODYHARD)
SHELF LIFE:	12 Months

The above information is reliable and accurate to the best of our knowledge at the time of preparation. Any recommendations or suggestions made are without warranty or guarantee. Users assume all responsibility since the conditions of use are beyond our control.

REVISED: 05 July 2013

REPLACES ISSUE: 1 December 2004