



TECHNICAL DATA SHEET

JET ACRYLIC BLACK

(SPRAYPAK)

PRODUCT DESCRIPTION

Concept Paint's Jet Acrylic Black Spraypak with its high gloss and opacity is ideally suited as a topcoat acrylic for automotive components. The use of special raw materials ensures excellent adhesion and long term durability.

PRODUCT AND ADDITIVES

- Concept Jet Acrylic Black Spraypak

SUITABLE SUBSTRATES

- Concept Acrylic Primer Spraypak
- Concept 1K Etch Primer Spraypak
- Sound existing surfaces, except for weak surfaces such as nitrocellulose or enamels.

SUBSTRATE PREPARATION

- All surfaces must be thoroughly sanded and cleaned with Concept Wax & Grease Remover prior to application.
- Mask off surrounding areas to avoid overspray.

MIXING

- Ready for Use
- Invert and shake the can thoroughly, until the agitation ball can be heard (two to three minutes). Continue to shake the can during application.

APPLICATION

- Spray in an even overlapping pattern from a distance of approximately 25 centimetres.
- Apply two to three even coats to gradually increase film thickness.
- Avoid heavy coats which may run.
- Allow 5 minutes flash off between coats.

Drying @ 25°C:	30 - 40 Minutes
-----------------------	-----------------

AFTER USE

- Turn the can upside down and spray until the jet clears.
- Any over spray maybe cleaned up with Mineral Turps.

TECHNICAL INFORMATION

COLOUR: Black

COVERAGE: 3m²/400g @ 25 Micron Dry Film Thickness.

PACKAGING: 400g

ITEM CODE:

SHELF LIFE: 12 Months

The above information is reliable and accurate to the best of our knowledge at the time of preparation. Any recommendations or suggestions made are without warranty or guarantee. Users assume all responsibility since the conditions of use are beyond our control.

REVISED: 22 May 2015

REPLACES ISSUE: 27 March 2015