



TECHNICAL DATA SHEET

UNIQUE ACRYLIC CLEAR

PRODUCT DESCRIPTION

Unique Acrylic Clear with its high gloss and UV protection is ideal as a clear coat for metallic based acrylic automotive paints. The use of special raw materials ensures a glossy flexible product, with excellent adhesion and durability.

PRODUCT AND ADDITIVES

- Concept Unique Acrylic Clear
- Concept Acrylic Thinner
- Concept Retarder Thinner




SUITABLE SUBSTRATES

- Concept Unicryl 3000 series.

MIXING RATIO





- 1 part Unique Acrylic Clear by volume.
- 1½ parts Acrylic Thinner by volume.
- If needed add 5 – 10% Retarder Thinner by volume to minimise blooming.

SPRAY GUN AND PRESSURE

SPRAY GUN & PRESSURE:	<ul style="list-style-type: none">• Gravity/Suction feed 2.00mm tip• Pressure low at 350kPa.	
-----------------------	---	---

APPLICATION

- All surfaces must be thoroughly sanded and cleaned with Concept Wax & Grease Remover prior to application.
- Apply two to three even coats.

SPRAYING VISCOSITY:	<ul style="list-style-type: none"> • 18 – 19 seconds B4 cup at 25°C. 	 18-19 SECONDS
FLASH-OFF TIME:	<ul style="list-style-type: none"> • 5 minutes between coats at 25°C. 	
DRYING:	<ul style="list-style-type: none"> • 40 – 60 minutes at 25°C for a Dry Film Thickness of 40 – 50 Micron. 	
SANDING:	<ul style="list-style-type: none"> • Sand with P1200 before buffing. 	

TECHNICAL INFORMATION

COLOUR:	Crystal Clear
COVERAGE:	5 m ² /L @ 50 Micron Dry Film Thickness.
VOC:	629 g/L
GLOSS:	Full
PACKAGING:	1LT, 4LT, 20LT
ITEM CODE:	A07C/CLR
SHELF LIFE:	12 Months

The above information is reliable and accurate to the best of our knowledge at the time of preparation. Any recommendations or suggestions made are without warranty or guarantee. Users assume all responsibility since the conditions of use are beyond our control.

REVISED: 15 April 2013

REPLACES ISSUE: 1 December 2004