



# TECHNICAL DATA SHEET

## UNIVERSAL FLATTENING BASE

### PRODUCT DESCRIPTION

Concept's Universal Flattening Base has been specifically designed for use with Concept's entire product range. It can reduce the gloss of any product without affecting the properties of that product. It produces a flattened even paint film that has excellent flow and adhesion.

### PRODUCT AND ADDITIVES

- Concept Universal Flattening Base
- Concept Entire Product Range

### SUITABLE SUBSTRATES

- *Refer to the relevant Technical Data Sheet for suitable Substrates.*

### MIXING RATIO

- Thoroughly stir Concept's Universal Flattening Base before use.

	<b>1K PRODUCT</b>	<b>2K PRODUCT</b>
<b>SATIN FINISH</b> (GLOSS:40 – 50)	Add 30% of Universal Flattening Base before thinning.	Add 30% of Universal Flattening Base before adding hardener and before thinning.
<b>MATT FINISH</b> (GLOSS:10 – 20)	Add 45% of Universal Flattening Base before thinning.	Add 45% of Universal Flattening Base before adding hardener and before thinning.

- Stir well after mixing.
- Never add more than 50% of Concept Universal Flattening Base.
- Allow to flash off to desired flatness before applying second coat.

## APPLICATION

- *Refer to the relevant Technical Data Sheet for Application.*

## TECHNICAL INFORMATION

<b>VOC:</b>	622 g/L
<b>PACKAGING:</b>	1LT, 4LT
<b>ITEM CODE:</b>	A06C/UNIFLAT
<b>SHELF LIFE:</b>	12 Months

---

The above information is reliable and accurate to the best of our knowledge at the time of preparation. Any recommendations or suggestions made are without warranty or guarantee. Users assume all responsibility since the conditions of use are beyond our control.

**REVISED: 14 June 2013**

**REPLACES ISSUE: 12 September 2007**