

CONCEPT **PAINTS**®

TECHNICAL DATA SHEET

VINYLAC CLEAR

PRODUCT DESCRIPTION

This high gloss, quick drying clear is ideally suited as a topcoat on any vinyl, simulated leather or flexible surface. It has been designed to be very flexible with good durability, making it suitable for truck sidings.

PRODUCT AND ADDITIVES

- Concept Vinylac Clear


SUITABLE SUBSTRATES

- Concept Unicolour 308 Vinyl Base.
- Vinyl.
- Simulated leather.
- Truck sidings.

MIXING RATIO




- Supplied ready for use. No thinning required.

SPRAY GUN AND PRESSURE

SPRAY GUN & PRESSURE:	<ul style="list-style-type: none">• 1.2 - 1.5 mm through a suction feed.• Pressure is 350 – 450 kPa (gravity feed will apply)	
-----------------------	--	---

APPLICATION

- Ensure that all surfaces are clean and free from any contamination prior to application.
- All unpainted surfaces must be thoroughly cleaned with Concept Antistatic Cleaner prior to application.
- Apply three even coats

SPRAYING VISCOSITY:	<ul style="list-style-type: none"> • 18 – 22 seconds B4 cup at 25°C. 	 18 - 22 SECONDS
FLASH-OFF TIME:	<ul style="list-style-type: none"> • 5 – 10 minutes between coats at 25°C. 	
DRYING:	60 – 90 minutes at 25°C for a Dry Film Thickness of 40 – 50 Micron.	

TECHNICAL INFORMATION

COLOUR:	Clear
COVERAGE:	3 m ² /L @ 50 Micron Dry Film Thickness.
VOC:	740 g/L
PACKAGING:	1LT, 4LT
ITEM CODE:	A07C/VC
SHELF LIFE:	12 Months

The above information is reliable and accurate to the best of our knowledge at the time of preparation. Any recommendations or suggestions made are without warranty or guarantee. Users assume all responsibility since the conditions of use are beyond our control.

REVISED: 05 June 2015

REPLACES ISSUE: 20 May 2015

Vinylac Clear

Page 2 of 2