

SAFETY DATA SHEET

1. IDENTIFICATION

PRODUCT(S): NO MIX LOW VOC BASECOAT

- LV-01 Black
- LV-04 Bright Gold
- LV-07 Copper
- LV-12 Maroon
- LV-15 Green
- LV-18 Grey Black
- LV-21 Lime
- LV-23 Midnight Blue
- LV-29 Midnight Black
- LV-32 Yellow Gold
- LV-35 Port Wine
- LV-38 Special Red Maroon
- LV-42 Silk Silver
- LV-45 Silk Blue
- LV-48 Silk Copper
- LV-53 Organic Orange
- LV-56 Silver Dollar Bright Coarse
- LV-60 Stabiliser Additive
- LV-63 HS Special Yellow
- LV-67 Coarse Metallic
- LV-70 Silver
- LV-74 Coarse Aluminium
- LV-78 White Sparkle Pearl
- LV-83 Orange Pearl
- LV-88 Fine Russet Pearl
- LV-91 Fine Blue Pearl
- LV-95 Blue Green Pearl
- LV-98 Fine Violet Pearl
- LV-102 Brandy Wine Candy
- LV-02 Blue
- LV-05 Bright Red
- LV-10 Deep Black
- LV-13 Deep Maroon
- LV-16 Green Blue
- LV-19 Empress Black
- LV-22 Magenta
- LV-24 Red Gold
- LV-30 Violet
- LV-33 Yellow Ochre
- LV-36 Deep Blue
- LV-39 HS Special Red
- LV-43 Silk Russet
- LV-46 Silk Red
- LV-51 Red Yellow
- LV-54 Special Silver Bright Fine
- LV-57 Silver Dollar Bright Fine
- LV-61 Effect White
- LV-65 Fine Metallic
- LV-68 Extra Fine Silver
- LV-71 Medium Silver
- LV-75 Extra Coarse Aluminium
- LV-80 Yellow Pearl
- LV-86 Copper Pearl
- LV-89 Blue Russet Pearl
- LV-92 Green Blue Pearl
- LV-96 Red Pearl
- LV-99 Metallic Raiser
- LV-103 Yellow Candy
- LV-03 Bright Blue
- LV-06 Custard
- LV-11 Cobalt Blue
- LV-14 Garnet
- LV-17 Green Gold
- LV-20 Light Red Oxide
- LV-25 Red Maroon
- LV-28 Turquoise
- LV-31 White
- LV-34 Special Violet
- LV-37 Special Deep Black
- LV-41 Reduced Black
- LV-44 Silk Gold
- LV-47 Silk Green
- LV-52 Topaz
- LV-55 Special Silver Coarse
- LV-59 Metallic Additive
- LV-62 HS White
- LV-66 Medium Metallic
- LV-69 Fine Silver
- LV-72 Coarse Silver
- LV-77 Fine White Pearl
- LV-82 Fine Yellow Gold Pearl
- LV-87 Bright Russet Pearl
- LV-90 Red Blue Pearl
- LV-93 Fine Green Pearl
- LV-97 Fine Silver Pearl
- LV-101 Red Candy
- LV-104 Green Candy

(This SDS encompasses any mixtures made from the above products.)

Supplier In Australia: Concept Paints
Address: 26 - 30 Charles Street, St Marys, Australia. 2760
Telephone Number: +61 2 96732555
Emergency Telephone: +61 2 96732555 (Monday to Friday 8am to 5pm)

Supplier In NZ: GPI Automotive (NZ) Ltd
Address: 59 Greenmount Drive, East Tamaki, Auckland, New Zealand
Telephone Number: +64 9 274 4943
Emergency Telephone: +64 9 274 4943 (Monday to Friday 8am to 5pm)

Recommended Use: Automotive Refinish

2. HAZARDS IDENTIFICATION

Classification:

- **HAZARDOUS SUBSTANCE.**
- **DANGEROUS GOODS.** (According to the criteria of ADG Code and NZ 5433.)

CLASSIFICATION	GHS CATEGORY	NZ CATEGORY	SIGNAL WORD	HAZARD STATEMENT
Flammable Liquids	2	3.1B	Warning	Highly flammable liquid and vapour.
Aspiration Hazard	1	6.1E (Aspiration Hazard)	Danger	May be fatal if swallowed and enters airways.
Skin Corrosion/ Irritation	2	6.3A	Warning	Causes skin irritation.
Eye Damage/ Irritation	2A	6.4A	Warning	Causes serious eye irritation.

Hazard Symbols:



Precautionary Statements:

- Keep away from heat/sparks/open flames/ hot surfaces. No smoking.
- Keep container tightly closed.
- Ground/bond container and receiving equipment.
- Use explosion-proof electrical/ventilation/lighting/equipment.
- Use only non-sparking tools.
- Take precautionary measures against static discharge.
- Wash hands thoroughly after handling.
- Wear protective gloves/protective clothing/eye protection/face protection.
- IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
- IF ON SKIN (or hair): Remove /take off immediately all contaminated clothing. Wash skin with plenty of soap and water.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.
- Specific treatment (see first aid instructions in this SDS).
- Specific measures (see first aid instructions in this SDS).
- DO NOT induce vomiting.
- If skin irritation occurs: Get medical advice/attention.
- If eye irritation persists: Get medical advice/attention.
- Take off contaminated clothing and wash before reuse.
- In case of fire: Use Foam, Carbon Dioxide or Dry Chemical Powder for extinction.
- Store in a well-ventilated place. Keep tightly closed. Keep cool.
- Store locked up.
- Dispose of contents/container in accordance with the relevant government legislation. Normally suitable for incineration by an approved agent.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Entity / Hazardous Component	CAS Numbers	Proportion by wt.
p-Chlorobenzotrifluoride	98-56-6	30 - 60%
Acetone	67-64-1	30 - 60%
Titanium Dioxide	13463-67-7	30 - 60%
Ethyl 3-Ethoxypropionate	763-69-9	10 - 30%
Methoxy Propyl Acetate	108-65-6	10 - 30%
Solvent Naphtha (petroleum), light arom.	64742-95-6	10 - 30%
Iron Oxide Fume	1309-37-1	<10%
Diacetone Alcohol	123-42-2	<10%
Mica	12001-26-2	<10%
Aluminium Metal Dust	7429-90-5	<10%
CI Pigment Yellow 83	5567-15-7	<10%
Solvent Naphtha (petroleum), heavy arom.	64742-94-5	<10%
Carbon Black	1333-86-4	<10%
N-Butyl Acetate	123-86-4	<10%
Naphtha (petroleum), hydrotreated heavy	64742-48-9	<10%
Xylene	1330-20-7	<10%
Silicon Dioxide, Chemically Prepared	112926-00-8	<10%
Graphite	7782-42-5	<10%
White Spirits (Stoddard Solvent)	8052-41-3	<10%
Dimethyl Glutarate	1119-40-0	<10%
CI Pigment Violet 23	6358-30-1	<10%
N-Butanol	71-36-3	<10%

This product(s) also contains 0 – 60% of other ingredients which are considered non-hazardous in accordance with ASCC/NOHSC and NZ HSNO criteria.

4. FIRST AID MEASURES

Route of Exposure First Aid Measures

Ingestion: Give a glass of water. Do NOT induce vomiting. Place patients head downwards if vomiting occurs. Prevent it entering lungs, as aspiration of material into the lungs can cause chemical pneumonitis which can be fatal. Immediately call a POISON CENTER or doctor/physician.

Eye: Immediately irrigate with large quantities of water for at least 15 minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Skin: Wash exposed area thoroughly with soap and water. Remove contaminated clothing. If skin irritation occurs: Get medical advice/attention.

Inhaled: Give fresh air, careful not to become a casualty yourself. Remove and loosen clothing. If breathing is normal make patient comfortable and keep warm till recovered. If breathing is difficult ensure the airways are clear and have a qualified person give oxygen from a face mask. If breathing has stopped commence (EAR) and if cardiac arrest has occurred, commence (CPR) and get medical advice/attention urgently.

Advice To Doctor: Treat Symptomatically.

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media: Foam, Carbon Dioxide or Dry Chemical Powder.

Hazards from Combustion Products: If involved in a fire, toxic materials such as carbon monoxide, carbon dioxide, nitrogen oxide, isocyanate vapour, traces of hydrogen cyanide, hydrogen chloride gas, hydrogen fluoride gas, various chlorine and/or fluorine compounds as well as hydrocarbons may form.

Precautions for Firefighters: Heating can cause rupture of containers with explosive force. If safe do so, remove all sources of ignition and any containers from the path of the fire. Keep cool with water spray.

Firefighters should wear self contained breathing apparatus with a full face and operated in the positive pressure mode.

Hazchem Code: 3[Y]E

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions: In case of an accidental release or spill, evacuate the danger area. Wear the correct Personal Protective Equipment (See section 8 of SDS). Do not breathe vapours. Extinguish all ignition sources and shut off the source of the spill. Ventilate the area.

Environmental Precautions: Avoid release to the environment by bunding or covering drains.

Containment: Contain and absorb the spill with absorbent material such as sand, soil or vermiculite. Transfer the material into drums, using non-sparking tools. Seal and label the drums. Contact the appropriate waste management authority for disposal.

7. HANDLING AND STORAGE

Precautions For Safe Handling: Wear the correct Personal Protective Equipment (See Section 8 of the SDS) when using this product. Ground the container and receiving equipment whilst using. Only use non-sparking tools and take precautionary measures against static discharge.

Only use in a well-ventilated area or preferably apply the product in a spray paint booth with an adequate exhaust system and explosion-proof electrical, ventilation, and lighting equipment.

Never eat, drink or smoke whilst handling this product. Always wash hands thoroughly after using this product and before smoking, eating, drinking or using the toilet.

Conditions For Safe Storage: Keep containers away from heat/sparks/open flames/ hot surfaces. Store containers in a well-ventilated area and away sources of ignition, oxidising agents and/or foodstuffs. Store containers in a cool place and out of direct sunlight. Keep containers tightly closed when not in use and check regularly for leaks.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits:	TLV –TWA (mg/m³)
p-Chlorobenzotrifluoride	Not Available
Acetone	1185
Titanium Dioxide	Not Available
Ethyl 3-Ethoxypropionate	Not Available
Methoxy Propyl Acetate	274
Solvent Naphtha (petroleum), light arom.	Not Available
Iron Oxide Fume	5
Diacetone Alcohol	238
Mica	2.5
Aluminium Metal Dust	10
CI Pigment Yellow 83	Not Available
Solvent Naphtha (petroleum), heavy arom.	Not Available
Carbon Black	3
N-Butyl Acetate	713
Naphtha (Petroleum) Hydrotreated Heavy	Not Available
Xylene	350
Silicon Dioxide, Chemically Prepared	2
Graphite	3
White Spirits (Stoddard Solvent)	790
Dimethyl Glutarate	Not Available
CI Pigment Violet 23	Not Available
N-Butanol	152

Engineering Controls: Ensure sufficient ventilation to maintain concentration below exposure standard. Only use in a well ventilated area or preferably apply the product in a spray paint booth with an adequate exhaust system. Keep containers sealed when not in use. Earth any mixing vessels when using this product.

Personal Protection: Skin contact should be avoided by wearing impervious work clothing, boots and Neoprene or PVC gloves. Eyes should be protected by chemical goggles or safety glasses fitted with side shields (Refer to AS/NZS 1337). If an inhalation risk exists, an organic vapour respirator or a self-contained breathing apparatus, with a full face and operated in the positive

pressure mode, should be used. Ensure cartridges are correct for the potential air contamination (Refer to AS/NZS 1715 and 1716).

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Viscous liquid of any colour.
Odour:	Strong solvent odour.
Odour Threshold:	Not Available
pH:	Not Applicable.
Melting Point/Freezing Point:	Not Applicable
Boiling Point Range:	56 – 175°C
Flash Point:	-18°C (Open Cup)
Evaporation Rate:	0.12 – 6.3 (Butyl Acetate = 1)
Flammability:	Highly flammable liquid and vapour.
Flammability Limits:	1 (LEL) to 13% (UEL) by volume
Vapour Pressure:	24.7 kPa @ 20°C
Vapour Density:	Not Available
Relative Density:	0.90 – 1.40
Solubility In Water:	Not Available
Partition Coefficient: n-octanol/water:	Not Available
Auto-ignition Temperature:	354°C
Decomposition Temperature:	Not Available
Viscosity:	<8,000 cps

10. STABILITY AND REACTIVITY

Reactivity: No applicable information is available.

Chemical Stability: Stable under ordinary conditions of use and storage.

Conditions to Avoid: Avoid all ignition sources.

Incompatible Materials: None

Hazardous Decomposition Products: If involved in a fire, toxic materials such as carbon monoxide, carbon dioxide, nitrogen oxide, isocyanate vapour, traces of hydrogen cyanide, hydrogen chloride gas, hydrogen fluoride gas and various chlorine and fluorine compounds and hydrocarbons may form.

Hazardous Reactions: Not Applicable.

11. TOXICOLOGICAL INFORMATION

There is no data available on this product itself. The following information (where available) relates to the individual ingredients of the product.

Acute Toxicity – Oral:

Ingredient	Value (LD50)	Species	GHS Category
Not Available			

Health Effects:

Acute:

Chronic:

Acute Toxicity – Dermal:

Ingredient	Value (LD50)	Species	GHS Category
Not Available			

Health Effects:

Acute:

Chronic:

Acute Toxicity – Inhalation:

Ingredient	Value (LC50)	Species	GHS Category
Not Available			

Health Effects:

Acute:

Chronic:

Skin Corrosion/Irritation:	GHS Category
p-Chlorobenzotrifluoride	2
Acetone	3
N-Butanol	3

Health Effects: Causes skin irritation.

Acute: Causes skin irritation.

Chronic: Repeated exposure may cause skin dryness and cracking. Also may cause dermatitis and eczema.

Eye Damage/Irritation:	GHS Category
Methoxy Propyl Acetate	2A
Acetone	2A
p-Chlorobenzotrifluoride	2A
N-Butanol	2A

Health Effects: Causes serious eye irritation.

Acute: Causes redness, tearing or blurred vision.

Chronic: Will cause discomfort and may cause redness, itching or blurred vision.

Respiratory or Skin Sensitation:	GHS Category
Not Available	

Health Effects:

Germ Cell Mutagenicity:	GHS Category
Not Available	

Health Effects:

Carcinogenicity:	GHS Category
Not Available	

Health Effects:

Toxic To Reproduction:	GHS Category
Not Available	

Health Effects:

Specific Target Organ Toxicity (Single Exposure):	GHS Category
Not Available	

Health Effects:

Specific Target Organ Toxicity (Repeated Exposure):	GHS Category
Not Available	

Health Effects:

Aspiration Hazard	GHS Category
Solvent Naphtha (petroleum), light arom.	1

Health Effects: May be fatal if swallowed and enters airways.

12. ECOLOGICAL INFORMATION

Environmental Precautions: Avoid release to the environment, the product should not be allowed to enter drains, water courses or the soil.

There is no data available on this product itself. The following information (where available) relates to the individual ingredients of the product.

Hazardous To The Aquatic Environment – Acute Hazard:

Ingredient	Value (LC50)	Species	GHS Category
Not Available			

Effects:

Hazardous To The Aquatic Environment – Long Term Hazard:

Ingredient	Value (LC50)	Species	GHS Category
Not Available			

Effects:

Exotoxic To Terrestrial Vertebrates:

Ingredient	Value (LD50)	Species	NZ Category
Not Available			

Effects:

Persistence and Degradability: No information available.

Bioaccumulative Potential: No information available.

Mobility in Soil: No information available.

13. DISPOSAL CONSIDERATIONS

Contact the relevant waste management authority. Normally suitable for incineration by an approved agent.

14. TRANSPORT INFORMATION

ADG (Land):

Shipping Name: PAINT
UN Number: 1263
Hazard Class: 3
Subsidiary Risk: Not Applicable
Packaging Group II
Hazchem 3[Y]E

NZS 5433:

Shipping Name: PAINT
UN Number: 1263
Hazard Class: 3
Subsidiary Risk: Not Applicable
Packaging Group II
Hazchem 3[Y]E

IMGD (Sea):

Shipping Name: PAINT
UN Number: 1263
Hazard Class: 3
Subsidiary Risk: Not Applicable
Packaging Group: II
Marine Pollutant: No
EmS: F-E,S-E

ICAO/IATA (Air):

Shipping Name: PAINT
UN Number: 1263
Hazard Class: 3
Subsidiary Risk: Not Applicable
Packaging Group II

15. REGULATORY INFORMATION

Poisons Schedule: Schedule 5
HSNO Group Standard: HSR002662 - Surface Coatings and Colourants
(Flammable)

16. OTHER INFORMATION

Date of Issue: 10/05/17
Replaces Issue Dated: 08/08/16

The above information has been presented in good faith and is accurate to the best of our knowledge, at the time of preparation. All of the information supplied herein is related only to the health and safety issues of the product. Users should assume all responsibility for its use, as the conditions under which this product is used are beyond our control. For technical information on the use of this product users should consult the appropriate Technical Data Sheet.

END OF SDS