

## SAFETY DATA SHEET

### 1. IDENTIFICATION

**PRODUCT(S): 456 HAMMERTONE BLACK**

**Supplier In Australia:** Concept Paints  
**Address:** 26 - 30 Charles Street, St Marys, Australia. 2760  
**Telephone Number:** +61 2 96732555  
**Emergency Telephone:** +61 2 96732555 (Monday to Friday 8am to 5pm)

**Supplier In NZ:** GPI Automotive (NZ) Ltd  
**Address:** 59 Greenmount Drive, East Tamaki, Auckland, New Zealand  
**Telephone Number:** +64 9 274 4943  
**Emergency Telephone:** +64 9 274 4943 (Monday to Friday 8am to 5pm)

**Recommended Use:** Commercial and Industrial Coating

### 2. HAZARDS IDENTIFICATION

**Classification:**

- **HAZARDOUS SUBSTANCE.**
- **DANGEROUS GOODS.** (According to the criteria of ADG Code and NZ 5433.)

| CLASSIFICATION              | GHS CATEGORY | NZ CATEGORY              | SIGNAL WORD | HAZARD STATEMENT                              |
|-----------------------------|--------------|--------------------------|-------------|---|
| Flammable Liquids           | 3            | 3.1C                     | Warning     | Flammable liquid and vapour.                  |
| Acute Toxicity – Oral       | 4            | 6.1D (Oral)              | Warning     | Harmful if swallowed.                         |
| Aspiration Hazard           | 1            | 6.1E (Aspiration Hazard) | Danger      | May be fatal if swallowed and enters airways. |
| Acute Toxicity – Dermal     | 4            | 6.1D (Dermal)            | Warning     | Harmful in contact with skin.                 |
| Skin Corrosion/ Irritation  | 2            | 6.3A                     | Warning     | Causes skin irritation.                       |
| Eye Damage/ Irritation      | 2A           | 6.4A                     | Warning     | Causes serious eye irritation.                |
| Acute Toxicity – Inhalation | 4            | 6.1D (Inhalation)        | Warning     | Harmful if inhaled.                           |

|   |   |                                     |         |  |
|---|---|-------------------------------------|---------|--|
| Specific Target Organ Toxicity (Single Exposure)        | 3 | 6.9<br>(Respiratory tract irritant) | Warning | May cause respiratory irritation.                                  |
| Toxic To Reproduction                                   | 2 | 6.8B                                | Warning | Suspected of damaging fertility or the unborn child.               |
| Specific Target Organ Toxicity (Repeated Exposure)      | 2 | 6.9B<br>(Repeated)                  | Warning | May cause damage to organs through prolonged or repeated exposure. |
| Hazardous To The Aquatic Environment – Long Term Hazard | 4 | 9.1D                                | None    | May cause long lasting harmful effects to aquatic life.            |
| Exotoxic To Terrestrial Vertebrates                     |   | 9.3C                                | None    | Harmful to terrestrial vertebrates.                                |

**Hazard Symbols:**



**Precautionary Statements:**

- Obtain special instructions for use.
- Do not handle until all safety precautions have been read and understood.
- Keep away from heat/sparks/open flames/ hot surfaces. No smoking.
- Keep container tightly closed.
- Ground/bond container and receiving equipment.
- Use explosion-proof electrical/ventilation/lighting/equipment.
- Use only non-sparking tools.
- Take precautionary measures against static discharge.
- Do not breathe dust/fume/gas/mist/vapours/spray.
- Wash hands thoroughly after handling.
- Do not eat, drink or smoke when using this product.
- Use only outdoors or in a well-ventilated area.
- Avoid release to the environment.
- Wear protective gloves/protective clothing/eye protection/face protection.
- IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
- IF ON SKIN (or hair): Remove /take off immediately all contaminated clothing. Wash skin with plenty of soap and water.
- IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.
- IF exposed or concerned: Get medical advice/attention.
- Call a POISON CENTER or doctor/physician if you feel unwell.
- Specific treatment (see first aid instructions in this SDS).
- Rinse mouth.
- DO NOT induce vomiting.
- If skin irritation occurs: Get medical advice/attention.
- If eye irritation persists: Get medical advice/attention.
- Take off contaminated clothing and wash before reuse.
- In case of fire: Use Foam, Carbon Dioxide or Dry Chemical Powder for extinction.

- Store in a well-ventilated place. Keep cool.
- Store locked up.
- Dispose of contents/container in accordance with the relevant government legislation. Normally suitable for incineration by an approved agent.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

| Chemical Entity / Hazardous Component    | CAS Numbers | Proportion by wt. |
|--|-------------|-------------------|
| Xylene                                   | 1330-20-7   | 20 - 40%          |
| Toluene                                  | 108-88-3    | 10 - 30%          |
| Solvent Naphtha (petroleum), light arom. | 64742-95-6  | 10 - 30%          |

This product(s) also contains 30 – 60% of other ingredients which are considered non-hazardous in accordance with ASCC/NOHSC and NZ HSNO criteria.

### 4. FIRST AID MEASURES

| Route of Exposure        | First Aid Measures  |
|--------------------------|---|
| <b>Ingestion:</b>        | Give a glass of water. Do NOT induce vomiting. Place patients head downwards if vomiting occurs. Prevent it entering lungs, as aspiration of material into the lungs can cause chemical pneumonitis which can be fatal. Immediately call a POISON CENTER or doctor/physician.   |
| <b>Eye:</b>              | Immediately irrigate with large quantities of water for at least 15 minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. If eye irritation persists: Get medical advice/attention.   |
| <b>Skin:</b>             | Wash exposed area thoroughly with soap and water. Remove contaminated clothing. If skin irritation occurs: Get medical advice/attention.  |
| <b>Inhaled:</b>          | Give fresh air, careful not to become a casualty yourself. Remove and loosen clothing. If breathing is normal make patient comfortable and keep warm till recovered. If breathing is difficult ensure the airways are clear and have a qualified person give oxygen from a face mask. If breathing has stopped commence (EAR) and if cardiac arrest has occurred, commence (CPR) and get medical advice/attention urgently. |
| <b>Advice To Doctor:</b> | Treat Symptomatically.  |

## 5. FIRE FIGHTING MEASURES

**Suitable Extinguishing Media:** Foam, Carbon Dioxide or Dry Chemical Powder.

**Hazards from Combustion Products:** If involved in a fire, toxic materials such as carbon monoxide, carbon dioxide, nitrogen oxide, isocyanate vapour, traces of hydrogen cyanide, hydrogen chloride gas, hydrogen fluoride gas, various chlorine and/or fluorine compounds as well as hydrocarbons may form.

**Precautions for Firefighters:** Heating can cause rupture of containers with explosive force. If safe do so, remove all sources of ignition and any containers from the path of the fire. Keep cool with water spray.

Firefighters should wear self contained breathing apparatus with a full face and operated in the positive pressure mode.

**Hazchem Code:** 3[Y]E

## 6. ACCIDENTAL RELEASE MEASURES

**Personal Precautions:** In case of an accidental release or spill, evacuate the danger area. Wear the correct Personal Protective Equipment (See section 8 of SDS). Do not breathe vapours. Extinguish all ignition sources and shut off the source of the spill. Ventilate the area.

**Environmental Precautions:** Avoid release to the environment by bunding or covering drains.

**Containment:** Contain and absorb the spill with absorbent material such as sand, soil or vermiculite. Transfer the material into drums, using non-sparking tools. Seal and label the drums. Contact the appropriate waste management authority for disposal.

## 7. HANDLING AND STORAGE

**Precautions For Safe Handling:** Wear the correct Personal Protective Equipment (See Section 8 of the SDS) when using this product. Ground the container and receiving equipment whilst using. Only use non-sparking tools and take precautionary measures against static discharge.

Only use in a well-ventilated area or preferably apply the product in a spray paint booth with an adequate exhaust system and explosion-proof electrical, ventilation, and lighting equipment.

Never eat, drink or smoke whilst handling this product. Always wash hands thoroughly after using this product and before smoking, eating, drinking or using the toilet.

**Conditions For Safe Storage:** Keep containers away from heat/sparks/open flames/ hot surfaces. Store containers in a well-ventilated area and away sources of ignition, oxidising agents and/or foodstuffs. Store containers in a cool place and out of direct sunlight. Keep containers tightly closed when not in use and check regularly for leaks.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

| Exposure Limits:                         | TLV –TWA (mg/m <sup>3</sup> ) |
|--|-------------------------------|
| Xylene                                   | 350                           |
| Toluene                                  | 191                           |
| Solvent Naphtha (petroleum), light arom. | Not Available                 |

**Engineering Controls:** Ensure sufficient ventilation to maintain concentration below exposure standard. Only use in a well ventilated area or preferably apply the product in a spray paint booth with an adequate exhaust system. Keep containers sealed when not in use. Earth any mixing vessels when using this product.

**Personal Protection:** Skin contact should be avoided by wearing impervious work clothing, boots and Neoprene or PVC gloves. Eyes should be protected by chemical goggles or safety glasses fitted with side shields (Refer to AS/NZS 1337). If an inhalation risk exists, an organic vapour respirator or a self-contained breathing apparatus, with a full face and operated in the positive pressure mode, should be used. Ensure cartridges are correct for the potential air contamination (Refer to AS/NZS 1715 and 1716).

## 9. PHYSICAL AND CHEMICAL PROPERTIES

|   |                                     |
|---|-------------------------------------|
| Appearance:                             | Black coloured viscous liquid.      |
| Odour:                                  | Strong solvent odour.               |
| Odour Threshold:                        | Not Available                       |
| pH:                                     | Not Applicable.                     |
| Melting Point/Freezing Point:           | Not Applicable                      |
| Boiling Point Range:                    | 95 – 175°C                          |
| Flash Point:                            | -15°C (Closed Cup)                  |
| Evaporation Rate:                       | 0.20 – 2.70 (Butyl Acetate = 1)     |
| Flammability:                           | Highly flammable liquid and vapour. |
| Flammability Limits:                    | 1 (LEL) to 11% (UEL) by volume      |
| Vapour Pressure:                        | 4 kPa @ 20°C                        |
| Vapour Density:                         | Not Available                       |
| Relative Density:                       | 0.90 – 1.00                         |
| Solubility In Water:                    | Not Available                       |
| Partition Coefficient: n-octanol/water: | Not Available                       |
| Auto-ignition Temperature:              | 471°C                               |
| Decomposition Temperature:              | Not Available                       |
| Viscosity:                              | <1,000 cps                          |

## 10. STABILITY AND REACTIVITY

**Chemical Stability:** Stable under ordinary conditions of use and storage.

**Conditions to Avoid:** Avoid all ignition sources.

**Incompatible Materials:** None

**Hazardous Decomposition Products:** If involved in a fire, toxic materials such as carbon monoxide, carbon dioxide, nitrogen oxide, isocyanate vapour, traces of hydrogen cyanide, hydrogen chloride gas, hydrogen fluoride gas and various chlorine and fluorine compounds and hydrocarbons may form.

**Hazardous Reactions:** Not Applicable.

## 11. TOXICOLOGICAL INFORMATION

There is no data available on this product itself. The following information (where available) relates to the individual ingredients of the product.

### Acute Toxicity – Oral:

| Ingredient | Value (LD50) | Species | GHS Category |
|------------|--------------|---------|--------------|
| Xylene     | 1590 mg/kg   | Mouse   | 4            |

**Health Effects:** Harmful if swallowed.

**Acute:** Can result in headaches, nausea, vomiting and diarrhoea.

**Chronic:** May cause irritation to the mucous membranes of the digestive system. May result in damage to the liver and kidney, blood disorders and may affect the central nervous system.

---

### Acute Toxicity – Dermal:

| Ingredient | Value (LD50) | Species | GHS Category |
|------------|--------------|---------|--------------|
| Xylene     | >1700 mg/kg  | Rabbit  | 4            |

**Health Effects:** Harmful in contact with skin.

**Acute:** Causes skin irritation.

**Chronic:** May cause dermatitis and eczema.

---

### Acute Toxicity – Inhalation:

| Ingredient | Value (LC50) | Species | GHS Category |
|------------|--------------|---------|--------------|
| Xylene     | 6350 ppm     | Rat     | 5            |

**Health Effects:** Harmful if inhaled.

**Acute:** Vapour concentrations above exposure limits may be irritating to the respiratory tract, may cause headaches and dizziness. Prolonged exposure may result in unconsciousness.

**Chronic:** Vapour concentrations above exposure limits may cause irritation to the mucous membranes of the respiratory system. May result in damage to the liver and kidney, blood disorders and may affect the central nervous system.

---

| Skin Corrosion/Irritation: | GHS Category |
|----------------------------|--------------|
| Toluene                    | 2            |
| Xylene                     | 2            |

**Health Effects:** Causes skin irritation.

**Acute:** Causes skin irritation.

**Chronic:** May cause dermatitis and eczema.

**Eye Damage/Irritation:**  
Xylene

**GHS Category**  
2A

**Health Effects:** Causes serious eye irritation.

**Acute:** Causes redness, tearing or blurred vision.

**Chronic:** Will cause discomfort and may cause redness, itching or blurred vision.

---

**Respiratory or Skin Sensitation:**  
Not Available

**GHS Category**

**Health Effects:**

---

**Germ Cell Mutagenicity:**  
Not Available

**GHS Category**

**Health Effects:**

---

**Carcinogenicity:**  
Not Available

**GHS Category**

**Health Effects:**

---

**Toxic To Reproduction:**  
Toluene  
Xylene

**GHS Category**  
1  
2

**Health Effects:** May damage fertility or the unborn child.

---

**Specific Target Organ Toxicity (Single Exposure):**  
Xylene

**GHS Category**  
3

**Health Effects:** May cause respiratory irritation.

---

**Specific Target Organ Toxicity (Repeated Exposure):**  
Toluene  
Xylene

**GHS Category**  
2  
2

**Health Effects:** May cause damage to organs through prolonged or repeated exposure.

---

**Aspiration Hazard**  
Toluene  
Solvent Naphtha (petroleum), light arom.

**GHS Category**  
1  
1

**Health Effects:** May be fatal if swallowed and enters airways.



## 12. ECOLOGICAL INFORMATION

**Environmental Precautions:** Avoid release to the environment, the product should not be allowed to enter drains, water courses or the soil.

There is no data available on this product itself. The following information (where available) relates to the individual ingredients of the product.

### Hazardous To The Aquatic Environment – Acute Hazard:

| Ingredient    | Value (LC50) | Species | GHS Category |
|---------------|--------------|---------|--------------|
| Not Available |              |         |              |

**Effects:**

---

### Hazardous To The Aquatic Environment – Long Term Hazard:

| Ingredient | Value (LC50)  | Species    | GHS Category |
|------------|---------------|------------|--------------|
| Xylene     | 8.5 mg/L 48hr | Crustacean | 4            |
| Xylene     | 3.3 mg/L 96hr | Fish       | 4            |
| Xylene     | 10 mg/L 72hr  | Algae      | 4            |

**Effects:** May cause long lasting harmful effects to aquatic life.

---

### Exotoxic To Terrestrial Vertebrates:

| Ingredient | Value (LD50) | Species | NZ Category |
|------------|--------------|---------|-------------|
| Xylene     | 1590 mg/kg   | Mouse   | 9.3C        |

**Effects:** Harmful to terrestrial vertebrates.

---

**Persistence and Degradability:** No information available.

**Bioaccumulative Potential:** No information available.

**Mobility in Soil:** No information available.

### 13. DISPOSAL CONSIDERATIONS

Contact the relevant waste management authority. Normally suitable for incineration by an approved agent.

### 14. TRANSPORT INFORMATION

**ADG (Land):**

Shipping Name: PAINT  
UN Number: 1263  
Hazard Class: 3  
Subsidiary Risk: Not Applicable  
Packaging Group II  
Hazchem 3[Y]E

**NZS 5433:**

Shipping Name: PAINT  
UN Number: 1263  
Hazard Class: 3  
Subsidiary Risk: Not Applicable  
Packaging Group II  
Hazchem 3[Y]E

**IMGD (Sea):**

Shipping Name: PAINT  
UN Number: 1263  
Hazard Class: 3  
Subsidiary Risk: Not Applicable  
Packaging Group: II  
Marine Pollutant: No  
EmS: F-E,S-E

**ICAO/IATA (Air):**

Shipping Name: PAINT  
UN Number: 1263  
Hazard Class: 3  
Subsidiary Risk: Not Applicable  
Packaging Group II

### 15. REGULATORY INFORMATION

Poisons Schedule: Schedule 6  
HSNO Group Standard: HSR002662 - Surface Coatings and Colourants  
(Flammable)

### 16. OTHER INFORMATION

Date of Issue: 16/01/19  
Replaces Issue Dated:

The above information has been presented in good faith and is accurate to the best of our knowledge, at the time of preparation. All of the information supplied herein is related only to the health and safety issues of the product. Users should assume all responsibility for its use, as the conditions under which this product is used are beyond our control. For technical information on the use of this product users should consult the appropriate Technical Data Sheet.

**END OF SDS**