

# Technical Data Sheet


<b>Product Name</b>	
Full Product Name	<b>469 Body Deadener Schutz &amp; Brushable</b>
Type of Product	1K 469 Body Deadener Schutz Spray and Brushable
Description	Concept 469 Body Deadener Schutz or Brushable is a flexible coating for sound deadening which protects against stone chips and corrosion. Great for underbody, bonnets, boots lids, underneath panels and mudguards.










<b>Products</b>				
Product Name	Volume Solids %	Weight Solids %	Density g/mL lbs/US gal	VOC g/L lbs/US gal
469 Body Deadener	55.8	64.8	1.090 8.99	409.0 3.40

<b>Properties</b>
<ul style="list-style-type: none"> <li>• Quick drying</li> </ul>
<ul style="list-style-type: none"> <li>• Flexible</li> </ul>
<ul style="list-style-type: none"> <li>• Textured finish</li> </ul>



<b>Substrates</b>
<ul style="list-style-type: none"> <li>• Metal surfaces primed with Concept 103 Etch Primer</li> </ul>
<ul style="list-style-type: none"> <li>• Existing finishes in sound condition</li> </ul>

# Technical Data Sheet

Substrate Preparation	
 <b>All Substrates</b>	<ul style="list-style-type: none"> <li>All surfaces must be thoroughly sanded and cleaned with Concept Wax &amp; Grease Remover prior to application.</li> <li>Lightly rusted surfaces must be treated with Concept 025 Rust Converter.</li> <li>Mask off surrounding areas to avoid overspray. Avoid spraying functional parts such as springs, exhausts, drive shafts, etc.</li> </ul>

Product Preparation				
 <b>Reducer</b>	If required thin with Concept 808 Multi Thinner for spraying.			
 <b>Pot life @ 25°C (77°F)</b>	N/A			
 <b>Spray viscosity @ 25°C (77°F)</b>	<b>BSB 4 Cup</b> <b>Ford 4 Cup</b>	As is		
 <b>Spray equipment</b>	<b>Gun type</b>	<b>Fluid tip</b>	<b>Spray pressure</b>	<b>Spray Distance</b>
	<b>Wide bore schutz gun</b>	4 mm 0.16"	345-690 kPa 3.45-6.9 bar 50-100 psi	15-20 cm 6-8 inch
 <b>Application</b>	Using a brush, apply one or two even coats. Avoid heavy wet coats.			
 <b>Number of coats</b>	2-3	Spray in an even overlapping pattern. Apply two to three even coats to gradually increase film thickness.		
 <b>DFT Recommended</b>	80-100 µm 3.2-4.0 mils			
 <b>Flash off time @ 25°C (77°F)</b>	5 min between coats			
 <b>Drying</b>	<b>Air Dry @ 25°C (77°F)</b>	3-4 hours		
<p>This data relates only to the material designated herein and does not apply to use in combination with any other material or any process. The data is not to be considered as a warranty or quality specification and we assume no liability in connection with its use.</p>				

# Technical Data Sheet

Remarks	
	Stir products thoroughly or shake well each time before use.
	Surface temperature must always be a minimum of 3°C (5°F) above dew point.

Equipment Cleaning	
Use recommended Concept Paints 035 Gunwash	

Dry Film Properties	
	After 1 days drying, <u>when compared to similar technology products.</u>
Moisture resistance	Excellent
Texture look	Excellent
Corrosion Resistance	Excellent
Vibration and Noise Protection	Excellent

Product Data	
Colour	Black
Theoretical Coverage	Approx. 5.0 m <sup>2</sup> /L (205 ft <sup>2</sup> /US gal) @ recommended DFT
Shelf Life	36 months in an unopened container at room temperature, away from sunlight.

Product Packaging		
Product Code	Product Name	Package Size
AU46970190001	469 Body Deadener Schutz	1L
AU4697039000X	469 Body Deadener Brushable	1L, 4L
AU8089200000X	808 Multi Thinner	1L, 4L, 20L

## Safety

For automotive and industrial use only by professional painters. Not recommended for sale to, or use by the general public. Before using, read and follow all label and Safety Data Sheet (SDS) precautions. If mixed with other components, the mixture will have hazards of all individual components.

Read and understand the Guidelines for the Safe Handling and Use of Isocyanate Containing Paints, including the use of approved respiratory protection and Personal Protective Equipment. Use only in a well-ventilated approved spray booth, according to local regulations.

The information provided in this documentation has been carefully selected and arranged by us. It is based upon our best knowledge on the subject at the date of issuance. The Information is given for information purposes only. We are not liable for its correctness, accuracy and completeness. It is up to the user to check if the information is current and the product is suitable for its intended purpose. The intellectual property in this Information, including patents, trademarks and copyrights, is protected. All rights reserved.

We may modify and/ or discontinue operation of all or portions of this Information at any time in our sole discretion, without notice and assume no responsibility to update the Information. All rules set forth in this clause shall apply accordingly for any future changes and amendments.

This Technical Data Sheet supersedes all previous issues.

Concept Paints  
26-30 Charles Street  
St Marys NSW 2760  
Sydney, Australia

ph. +61 (2) 9673 2555  
fax. +61 (2) 9623 1918  
[office@conceptpaints.com.au](mailto:office@conceptpaints.com.au)  
[www.conceptpaints.com.au](http://www.conceptpaints.com.au)