

# Technical Data Sheet



Date: 22 February 2022

Version 3

Product Name	
Full Product Name	812 Brushable Thinner
Type of Product	Brushing thinner
Description	This is a brushing thinner designed to be used with our Concept Unicolour 600 2K, Concept Unicote 300 Polyurethane, Epoxy and Enamel range as well as Concept 401, 402, 403 and 404 topcoat products to enable application using a brush or roller by improving flow.

Products				
Product Name	Volume solids %	Weight solids %	Density g/mL lbs/US gal	VOC g/L lbs/US gal
812 Brushable Thinner	0.0	0.0	0.912 6.89	912.0 6.89




Properties	
<ul style="list-style-type: none"> <li>Improved flow ideal for brushing and rolling applications</li> <li>Quick and easy application</li> </ul>	
Substrates	Special Notes: <ul style="list-style-type: none"> <li>All surfaces must be thoroughly sanded and cleaned with Concept Wax &amp; Grease Remover prior to application.</li> <li>Use white or light-coloured primers under bright yellows, oranges and reds, if required.</li> </ul>

Product Preparation		
	Reducer	Up to 10% (v/v)
	DFT Recommended	50 µm 2.0 mils
This data relates only to the material designated herein and does not apply to use in combination with any other material or any process. The data is not to be considered as a warranty or quality specification and we assume no liability in connection with its use.		

# Technical Data Sheet

Date: 22 February 2022

Version 3

Remarks	
	Stir all products thoroughly each time before use. Stir the mixture well after the weigh-out of the components.
	Before application a colour comparison is recommended.
	Surface temperature must always be a minimum of 3°C (5°F) above dew point.

<b>Safety</b>	<p>For industrial use only by professional painters. Not recommended for sale to, or use by the general public. Before using, read and follow all label and Safety Data Sheet (SDS) precautions. If mixed with other components, the mixture will have hazards of all individual components.</p> <p>Read and understand the Guidelines for the Safe Handling and Use of Isocyanate Containing Paints, including the use of approved respiratory protection and Personal Protective Equipment. Use only in a well-ventilated approved spray booth, according to local regulations.</p>
---------------	---

The information provided in this documentation has been carefully selected and arranged by us. It is based upon our best knowledge on the subject at the date of issuance. The Information is given for information purposes only. We are not liable for its correctness, accuracy and completeness. It is up to the user to check if the information is current and the product is suitable for its intended purpose. The intellectual property in this Information, including patents, trademarks and copyrights, is protected. All rights reserved.

We may modify and/ or discontinue operation of all or portions of this Information at any time in our sole discretion, without notice and assume no responsibility to update the Information. All rules set forth in this clause shall apply accordingly for any future changes and amendments.  
This Technical Data Sheet supersedes all previous issues.

Concept Paints  
26-30 Charles Street  
St Marys NSW 2760  
AUSTRALIA

ph. +61 (2) 9673 2555  
fax. +61 (2) 9623 1918  
office@conceptpaints.com.au  
www.conceptpaints.com.au