








## 831 2K Thinner






### Thinner Selection Guide

#### Low Temperature Baking

Baking Temperature			25°C	30°C	35°C	40°C	45°C	50°C	55°C	60°C
			77°F	86°F	95°F	104°F	113°F	122°F	131°F	140°F
831 2K Thinner	Single Panel	Fast								
		Normal								
	Large areas	Fast								
		Normal								
		Slow								

 40 min
 35 min

#### Air Drying

Ambient Temperature			10°C	15°C	20°C	25°C	30°C	35°C	40°C	45°C
			50°F	59°F	68°F	77°F	86°F	95°F	104°F	113°F
831 2K Thinner	Single Panel	Fast								
		Normal								
	Large areas	Fast								
		Normal								
		Slow								

**Note:** Ensure that substrate temperature is at least 3°C (5°F) above Dew Point Temperature.

This guide is intended for use by professional trade and industrial applicators in compliance with relevant Health, Safety & Environmental standards and legislation. The applicator must use suitable Personal Protective Equipment (PPE), in particular full body coverall, gloves, goggles and air respirator, provide adequate ventilation when using in confined spaces.

For more detailed information, refer to Safety Data Sheets of the products used.

This information is issued by Concept Paints as a guidance only and is current and correct to the best of our knowledge at the time of issuance. The user must ensure suitability of the products and their performance for the application at hand. Concept Paints assumes no responsibility nor provides any warranty.