

Safety Data Sheet



Driven by Innovation

Hazardous, Dangerous Goods

1. MATERIAL AND SUPPLY COMPANY IDENTIFICATION

Product name: **Acrylic Wheel Silver Aerosol**

Recommended use: Touch up for Silver Wheels

Supplier: CHILMIX PTY LTD T/A CONCEPT PAINTS
ABN: 28 069 967 362
Street Address: 26 - 30 Charles Street
St Marys NSW 2760
Australia
Telephone: +61 2 9673 2555
Facsimile: +61 2 9623 1918
Email: office@conceptpaints.com.au

Emergency Telephone number: **+1 703 741 6037 (24 hours)**

2. HAZARDS IDENTIFICATION

This material is hazardous according to health criteria of Safe Work Australia.



Signal Word

Danger

Hazard Classifications

Aerosols - Category 1
Aspiration Hazard - Category 1
Eye Damage/Irritation - Category 2A
Reproductive Toxicity - Category 2
Specific Target Organ Toxicity (Single Exposure) - Category 3 Narcotic Effects
Specific Target Organ Toxicity (Repeated Exposure) - Category 2

Hazard Statements

H222 Extremely flammable aerosol.
H229 Pressurized container: may burst if heated.
H304 May be fatal if swallowed and enters airways.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H361 Suspected of damaging fertility or the unborn child .
H373 May cause damage to organs through prolonged or repeated exposure.

Prevention Precautionary Statements

P102 Keep out of reach of children.
P103 Read carefully and follow all instructions.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P211 Do not spray on an open flame or other ignition sources.
P251 Do not pierce or burn, even after use.
P260 Do not breathe dust, fume, gas, mist, vapours or spray.
P261 Avoid breathing dust, fume, gas, mist, vapours or spray..

Safety Data Sheet



Driven by Innovation

P264 Wash hands, face and all exposed skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/protective clothing including eye/face protection and suitable respirator.

Response Precautionary Statements

P101 If medical advice is needed, have product container or label at hand.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor For advice, contact a Poisons Information Centre (e.g. phone Australia 13 11 26; New Zealand 0800 764 766) or a doctor (at once)..
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 IF exposed or concerned: Get medical advice/attention.
P312 Call a POISON CENTER/doctor For advice, contact a Poisons Information Centre (e.g. phone Australia 13 11 26; New Zealand 0800 764 766) or a doctor (at once). if you feel unwell.
P314 Get medical advice/attention if you feel unwell.
P331 Do NOT induce vomiting.
P337+P313 If eye irritation persists: Get medical advice/attention.

Storage Precautionary Statements

P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P405 Store locked up.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Disposal Precautionary Statement

P501 Dispose of contents/container in accordance with local, regional, national and international regulations.

Poison Schedule: Unknown

DANGEROUS GOOD CLASSIFICATION

Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

Dangerous Goods Class: 2.1

3. COMPOSITION INFORMATION

CHEMICAL ENTITY	CAS NO	PROPORTION
Acetone	67-64-1	30 - 60 % (w/w)
Propane	74-98-6	20 - 30 % (w/w)
Butane	106-97-8	10 - 30 % (w/w)
Toluene	108-88-3	10 - 30 % (w/w)
Propanoic acid, 3-ethoxy-, ethyl ester	763-69-9	1 - 10 % (w/w)
Ingredients determined to be Non-Hazardous		Balance
		100%

4. FIRST AID MEASURES

If poisoning occurs, contact a doctor or Poisons Information Centre (Phone Australia 131 126, New Zealand 0800 764 766).

Inhalation: Remove victim from exposure - avoid becoming a casualty. Remove contaminated clothing and

Safety Data Sheet



Driven by Innovation

loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Seek medical advice if effects persist.

Skin Contact: If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. If swelling, redness, blistering or irritation occurs seek medical assistance. For gross contamination, immediately drench with water and remove clothing. Continue to flush skin and hair with plenty of water (and soap if material is insoluble). For skin burns, cover with a clean, dry dressing until medical help is available. If blistering occurs, do NOT break blisters. If swelling, redness, blistering, or irritation occurs seek medical assistance.

Eye contact: If in eyes, hold eyelids apart and flush the eyes continuously with running water. Continue flushing until advised to stop by the Poisons Information Centre or a Doctor; or for at least 15 minutes and transport to Doctor or Hospital.

Ingestion: Immediately rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water to drink. Never give anything by the mouth to an unconscious patient. If vomiting occurs give further water. Immediately call Poisons Centre or Doctor.

PPE for First Aiders: Wear safety shoes, overalls, gloves, safety glasses, respirator. Use with adequate ventilation. If inhalation risk exists wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Available information suggests that gloves made from polyvinyl chloride (PVC) should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

Notes to physician: Treat symptomatically.

5. FIRE FIGHTING MEASURES

Hazchem Code: 2YE

Suitable extinguishing media: If material is involved in a fire use water fog (or if unavailable fine water spray), alcohol resistant foam, standard foam, dry agent (carbon dioxide, dry chemical powder).

Specific hazards: Extremely flammable aerosol. May form flammable vapour mixtures with air. Flameproof equipment necessary in area where this chemical is being used. Nearby equipment must be earthed. Electrical requirements for work area should be assessed according to AS3000. Vapour may travel a considerable distance to source of ignition and flash back. Avoid all ignition sources. All potential sources of ignition (open flames, pilot lights, furnaces, spark producing switches and electrical equipment etc) must be eliminated both in and near the work area. Do NOT smoke.

Fire fighting further advice: Heating can cause expansion or decomposition leading to violent rupture of containers. If safe to do so, remove containers from path of fire. Keep containers cool with water spray. On burning or decomposing may emit toxic fumes. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion or decomposition.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILLS

Wear protective equipment to prevent skin and eye contamination. Avoid inhalation of gas. If safe to do so, isolate the leak. Increase ventilation to assist with dispersion.

LARGE SPILLS

If safe to do so, shut off all possible sources of ignition. Clear area of all unprotected personnel. Use a spark-free shovel. If safe to do so, isolate the leak. Increase ventilation to assist with dispersion. If contamination of crops, sewers or waterways has occurred advise local emergency services.

Dangerous Goods - Initial Emergency Response Guide No: 49

7. HANDLING AND STORAGE

Handling: Avoid eye contact and skin contact. Avoid inhalation of vapour, mist or aerosols.

Storage: Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from foodstuffs. Store away from incompatible materials described in Section 10. Store away from sources of heat and/or ignition. Store locked up. Do not expose to temperatures exceeding 50 °C/122 °F. Keep containers closed when not in use - check regularly for leaks.

This material is classified as a Division 2.1 Flammable Gas as per the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and/or the "New Zealand NZS5433: Transport of Dangerous Goods on Land" and must be stored in accordance with the relevant regulations.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

National occupational exposure limits:

	TWA		STEL		NOTICES
	ppm	mg/m3	ppm	mg/m3	
Acetone	500	1185	1000	2375	-
Butane	800	1900	-	-	-
Propane	-	-	-	-	-
Toluene	50	191	150	574	Sk

As published by Safe Work Australia.

TWA - The time-weighted average airborne concentration over an eight-hour working day, for a five-day working week over an entire working life.

STEL (Short Term Exposure Limit) - the average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight-hour workday.

'Sk' Notice - absorption through the skin may be a significant source of exposure. The exposure standard is invalidated if such contact should occur.

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

If the directions for use on the product label are followed, exposure of individuals using the product should not exceed the above standard. The standard was created for workers who are routinely, potentially exposed during product manufacture.

Biological Limit Values: As per the "National Model Regulations for the Control of Workplace Hazardous Substances (Safe Work Australia)" the ingredients in this material do not have a Biological Limit Allocated.

Engineering Measures: Ensure ventilation is adequate to maintain air concentrations below Exposure Standards. Use only in well ventilated areas. Use with local exhaust ventilation or while wearing appropriate respirator. Vapour heavier than air - prevent concentration in hollows or sumps. Do NOT enter confined spaces where vapour may have collected.

Personal Protection Equipment: SAFETY SHOES, OVERALLS, GLOVES, SAFETY GLASSES, RESPIRATOR.

Personal protective equipment (PPE) must be suitable for the nature of the work and any hazard associated with

Safety Data Sheet



Driven by Innovation

the work as identified by the risk assessment conducted.

Wear safety shoes, overalls, gloves, safety glasses, respirator. Use with adequate ventilation. If inhalation risk exists wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Available information suggests that gloves made from polyvinyl chloride (PVC) should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

Hygiene measures: Keep away from food, drink and animal feeding stuffs. When using do not eat, drink or smoke. Wash hands prior to eating, drinking or smoking. Avoid contact with clothing. Avoid eye contact and skin contact. Avoid inhalation of vapour, mist or aerosols. Ensure that eyewash stations and safety showers are close to the workstation location.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form:	Aerosol
Colour:	Silver Liquid
Odour:	Characteristic of Paint thinners
Solubility:	Insoluble in water
Specific Gravity:	0.91
Flash Point (°C):	<0
Total VOC (g/Litre):	850 g/l

(Typical values only - consult specification sheet)
N Av = Not available, N App = Not applicable

10. STABILITY AND REACTIVITY

Chemical stability: This material is thermally stable when stored and used as directed.

Conditions to avoid: Elevated temperatures and sources of ignition.

Incompatible materials: Oxidising agents.

Hazardous decomposition products: Oxides of carbon and nitrogen, smoke and other toxic fumes.

Hazardous reactions: No known hazardous reactions.

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Acute Effects

Inhalation: Material may be an irritant to mucous membranes and respiratory tract. Inhalation of vapour can result in headaches, dizziness and possible nausea. Inhalation of high concentrations can produce central nervous system depression, which can lead to loss of co-ordination, impaired judgement and if exposure is prolonged, unconsciousness.

Skin contact: Contact with skin may result in irritation.

Ingestion: Swallowing can result in nausea, vomiting and irritation of the gastrointestinal tract. May cause lung damage if swallowed. Small amounts of liquid aspirated into the respiratory system during ingestion or vomiting may cause bronchopneumonia or pulmonary oedema.

Safety Data Sheet



Driven by Innovation

Eye contact: An eye irritant.

Acute toxicity

Inhalation: This material has been classified as not hazardous for acute inhalation exposure. Acute toxicity estimate (based on ingredients): $LC_{50} > 20,000$ ppm for gases

Skin contact: This material has been classified as not hazardous for acute dermal exposure. Acute toxicity estimate (based on ingredients): $LD_{50} > 2,000$ mg/Kg bw

Ingestion: This material has been classified as not hazardous for acute ingestion exposure. Acute toxicity estimate (based on ingredients): $LD_{50} > 2,000$ mg/Kg bw

Corrosion/Irritancy: Eye: this material has been classified as a Category 2A Hazard (reversible effects to eyes). Skin: this material has been classified as not corrosive or irritating to skin.

Sensitisation: Inhalation: this material has been classified as not a respiratory sensitiser. Skin: this material has been classified as not a skin sensitiser.

Aspiration hazard: This material has been classified as Aspiration Hazard - Category 1

Specific target organ toxicity (single exposure): This material has been classified as a Category 3 Hazard. Exposure via inhalation may result in depression of the central nervous system.

Chronic Toxicity

Mutagenicity: This material has been classified as not a mutagen.

Carcinogenicity: This material has been classified as not a carcinogen.

Reproductive toxicity (including via lactation): This material has been classified as a Category 2 Hazard.

Specific target organ toxicity (repeat exposure): This material has been classified as a Category 2 Hazard.

12. ECOLOGICAL INFORMATION

Avoid contaminating waterways.

Acute aquatic hazard: This material has been classified as not hazardous for acute aquatic exposure. Acute toxicity estimate (based on ingredients): > 100 mg/L

Long-term aquatic hazard: This material has been classified as not hazardous for chronic aquatic exposure. Non-rapidly or rapidly degradable substance for which there are adequate chronic toxicity data available OR in the absence of chronic toxicity data, Acute toxicity estimate (based on ingredients): > 100 mg/L, where the substance is not rapidly degradable and/or $BCF < 500$ and/or $\log K_{ow} < 4$.

Ecotoxicity: No information available.

Persistence and degradability: No information available.

Bioaccumulative potential: No information available.

Mobility: No information available.

13. DISPOSAL CONSIDERATIONS

Persons conducting disposal, recycling or reclamation activities should ensure that appropriate personal

Safety Data Sheet



Driven by Innovation

protection equipment is used, see "Section 8. Exposure Controls and Personal Protection" of this SDS.

If possible material and its container should be recycled. If material or container cannot be recycled, dispose in accordance with local, regional, national and international Regulations.

14. TRANSPORT INFORMATION

ROAD AND RAIL TRANSPORT

Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".



UN No: 1950
Dangerous Goods Class: 2.1
Packing Group: None
Hazchem Code: 2YE
Emergency Response Guide No: 49

Proper Shipping Name: AEROSOLS

Segregation Dangerous Goods: Not to be loaded with explosives (Class 1), flammable liquids (Class 3), if both are in bulk, flammable solids (Class 4.1), spontaneously combustible substances (Class 4.2), dangerous when wet substances (Class 4.3), oxidising agents (Class 5.1), organic peroxides (Class 5.2) or radioactive substances (Class 7). Exemptions may apply.

MARINE TRANSPORT

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.



UN No: 1950
Dangerous Goods Class: 2.1
Packing Group: None

Proper Shipping Name: AEROSOLS

AIR TRANSPORT

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.



UN No: 1950
Dangerous Goods Class: 2.1
Packing Group: None

Safety Data Sheet



Driven by Innovation

Proper Shipping Name: AEROSOLS, FLAMMABLE

15. REGULATORY INFORMATION

This material is not subject to the following international agreements:

Montreal Protocol (Ozone depleting substances)
The Stockholm Convention (Persistent Organic Pollutants)
The Rotterdam Convention (Prior Informed Consent)
International Convention for the Prevention of Pollution from Ships (MARPOL)

This material is subject to the following international agreements:

Basel Convention (Hazardous Waste)
• Wastes from production, formulation and use of inks, dyes, pigments, paints, lacquers, varnish

This material/constituent(s) is covered by the following requirements:

AllICS Status: Formulations where all components AllC listed.

All components of this product are listed on or exempt from the New Zealand Inventory of Chemical (NZIoC).

HSNO Group Standard: HSR002515 - Aerosols (Flammable) Group Standard 2020

16. OTHER INFORMATION

Reason for issue: First Issue

This information was prepared in good faith from the best information available at the time of issue. It is based on the present level of research and to this extent we believe it is accurate. However, no guarantee of accuracy is made or implied and since conditions of use are beyond our control, all information relevant to usage is offered without warranty. The manufacturer will not be held responsible for any unauthorised use of this information or for any modified or altered versions.

If you are an employer it is your duty to tell your employees, and any others that may be affected, of any hazards described in this sheet and of any precautions that should be taken.

Safety Data Sheets are updated frequently. Please ensure you have a current copy.