


# Technical Data Sheet

Product Name	
Full Product Name	<b>Antistatic Cleaner</b>
Type of Product	Antistatic cleaner for plastics
Description	Concept Antistatic Cleaner is a solvent-based cleaner which cleans and helps to reduce any static charge from plastic substrates.

Products						
Product Name	Volume Solids	Weight Solids	Density		VOC	
	%	%	g/mL	lbs/US gal	g/L	lbs/US gal
Antistatic Cleaner	0.0	0.0	0.806	6.73	806.1	6.73

Properties
<ul style="list-style-type: none"> <li>Reduces static charge from plastics</li> <li>Ready for use</li> </ul>

Substrates
<ul style="list-style-type: none"> <li>Any plastic substrates suitable for painting. Always check first.</li> </ul>

Substrate Preparation	
 <b>All Substrates</b>	<ul style="list-style-type: none"> <li>Soak cloth thoroughly in Concept Antistatic Cleaner.</li> <li>Wipe area to be painted and allow the cleaner to dry.</li> <li>Apply Concept Plastic Primer.</li> </ul>

## Product Preparation



### Reducer

Not required – product supplied ready for use.

This data relates only to the material designated herein and does not apply to use in combination with any other material or any process. The data is not to be considered as a warranty or quality specification and we assume no liability in connection with its use.

## Remarks



Stir all products thoroughly each time before use.  
Stir the mixture well after the weigh-out of the components.



Surface temperature must always be a minimum of 3°C (5°F) above dew point.

## Equipment Cleaning

Use recommended Concept Paints 035 Gunwash

## Dry Film Properties

After 7 days drying,  
**when compared to similar technology products.**

Refer to the relevant Technical Data Sheet

## Product Data

Colour	Water white
Theoretical Coverage	Refer to the relevant Technical Data Sheet
Shelf Life	36 months in an unopened container at room temperature away from sunlight.

# Technical Data Sheet

## Product Packaging

Product Code	Product Name	Package Size
AU0289000000X	Antistatic Cleaner	1L, 4L

## Safety

For automotive and industrial use only by professional painters. Not recommended for sale to, or use by the general public. Before using, read and follow all label and Safety Data Sheet (SDS) precautions. If mixed with other components, the mixture will have hazards of all individual components.

Read and understand the Guidelines for the Safe Handling and Use of Isocyanate Containing Paints, including the use of approved respiratory protection and Personal Protective Equipment. Use only in a well-ventilated approved spray booth, according to local regulations.

The information provided in this documentation has been carefully selected and arranged by us. It is based upon our best knowledge on the subject at the date of issuance. The Information is given for information purposes only. We are not liable for its correctness, accuracy and completeness. It is up to the user to check if the information is current and the product is suitable for its intended purpose. The intellectual property in this Information, including patents, trademarks and copyrights, is protected. All rights reserved.

We may modify and/ or discontinue operation of all or portions of this Information at any time in our sole discretion, without notice and assume no responsibility to update the Information. All rules set forth in this clause shall apply accordingly for any future changes and amendments.

This Technical Data Sheet supersedes all previous issues.

Concept Paints  
26-30 Charles Street  
St Marys NSW 2760  
Sydney, Australia

ph. +61 (2) 9673 2555  
fax. +61 (2) 9623 1918  
office@conceptpaints.com.au  
www.conceptpaints.com.au