











Product Name	
Full Product Name	Basecoat Reducer
Type of Product	1K basecoat reducer
Description	Concept Basecoat Reducer is a 1K basecoat reducer developed specifically to promote the application of all Concept 1K basecoats.

Products					
Basecoat Reducer	Volume Solids	Weight Solids	Density		VOC
	%	%	g/mL	lbs/US gal	g/L lbs/US gal
Basecoat Reducer	0.0	0.0	0.879	7.33	878.9 7.33



Suitable for
<ul style="list-style-type: none"> Concept Basecoats

Substrate Preparation	
 All Substrates	Refer to the relevant Technical Data Sheet for base product.

Product Preparation

	Mixing Ratio (by volume)	Refer to the relevant Technical Data Sheet for base product.			
	Reducer	Refer to the relevant Technical Data Sheet for base product.			
	Pot life @ 25°C (77°F)	Refer to the relevant Technical Data Sheet for base product.			
	Spray viscosity @ 25°C (77°F)	BSB 4 Cup Ford 4 Cup	Refer to the relevant Technical Data Sheet for base product.		
	Spray equipment	Gun Type	Fluid Tip	Spray Pressure	Spray Distance
		Refer to the relevant Technical Data Sheet for base product.			
	Number of coats	Refer to the relevant Technical Data Sheet for base product.			
	DFT Recommended	Refer to the relevant Technical Data Sheet for base product.			
	Flash off time @ 25°C (77°F)	Refer to the relevant Technical Data Sheet for base product.			
	Drying	Refer to the relevant Technical Data Sheet for base product.			
This data relates only to the material designated herein and does not apply to use in combination with any other material or any process. The data is not to be considered as a warranty or quality specification and we assume no liability in connection with its use.					

Remarks

	Stir all products thoroughly each time before use. Stir the mixture well after the weigh-out of the components.
	Surface temperature must always be a minimum of 3°C (5°F) above the dew point.

Equipment Cleaning

Use recommended Concept cleaner.

Dry Film Properties

After 7 days drying,
when compared to similar technology products.

Refer to the relevant Technical Data Sheet for base product.

Product Data

Colour	Water white.
Theoretical Coverage	Refer to the relevant Technical Data Sheet for base product.
Shelf Life	36 months in an unopened container at room temperature, away from sunlight.

Product Packaging

Product Code 1	Product Name	Package Size
AU803920000XX	Basecoat Reducer	1L, 4L, 20L
AU80391000004	Slow Basecoat Reducer	4L

Safety

For automotive and industrial use only by professional painters. Not recommended for sale to, or use by the general public. Before using, read and follow all label and Safety Data Sheet (SDS) precautions. If mixed with other components, the mixture will have hazards of all individual components.

Read and understand the Guidelines for the Safe Handling and Use of Isocyanate Containing Paints, including the use of approved respiratory protection and Personal Protective Equipment. Use only in a well-ventilated approved spray booth, according to local regulations

The information provided in this documentation has been carefully selected and arranged by us. It is based upon our best knowledge on the subject at the date of issuance. The information is given for information purposes only. We are not liable for its correctness, accuracy and completeness. It is up to the user to check if the information is current and the product is suitable for its intended purpose. The intellectual property in this information, including patents, trademarks and copyrights, is protected. All rights reserved.

We may modify and/or discontinue operation of all or portions of this information at any time in our sole discretion, without notice and assume no responsibility to update the information. All rules set forth in this clause shall apply accordingly for any future changes and amendments.

This Technical Data Sheet supersedes all previous issues.

Concept Paints
26-30 Charles Street
St Marys NSW 2760
Sydney, Australia

ph. +61 (2) 9673 2555
fax. +61 (2) 9623 1918
office@conceptpaints.com.au
www.conceptpaints.com.au