

SAFETY DATA SHEET

1. IDENTIFICATION

PRODUCT(S): FADEOUT THINNER

Supplier In Australia: Concept Paints

Address: 26 - 30 Charles Street, St Marys, Australia. 2760

Telephone Number: +61 2 96732555

Emergency Telephone: +61 2 96732555 (Monday to Friday 8am to 5pm)

Supplier In NZ: GPI Automotive (NZ) Ltd

Address: 59 Greenmount Drive, East Tamaki, Auckland, New Zealand

Telephone Number: +64 9 274 4943

Emergency Telephone: +64 9 274 4943 (Monday to Friday 8am to 5pm)

Recommended Use: Aerosol for Industrial and Commercial Use

2. HAZARDS IDENTIFICATION

Classification:

- HAZARDOUS SUBSTANCE.
- DANGEROUS GOODS. (According to the criteria of ADG Code and NZ 5433.)

CLASSIFICATION	GHS CATEGORY	NZ CATEGORY	SIGNAL WORD	HAZARD STATEMENT	
Flammable Aerosols	1	2.1.2A	Danger	Extremely flammable aerosol.	
Eye Damage/ Irritation	2A	6.4A	Warning	Causes serious eye irritation.	

Fadeout Thinner Page 1 of 10

Hazard Symbols:





Precautionary Statements:

- Keep away from heat/sparks/open flames/ hot surfaces. No smoking.
- Do not spray on an open flame or other ignition source.
- Keep container tightly closed.
- Ground/bond container and receiving equipment.
- Use explosion-proof electrical/ventilation/lighting/equipment.
- Use only non-sparking tools.
- Take precautionary measures against static discharge.
- Pressurised container; do not pierce or burn, even after use.
- Wash hands thoroughly after handling.
- Wear protective gloves/protective clothing/eye protection/face protection.
- IF ON SKIN (or hair): Remove /take off immediately all contaminated clothing. Wash skin with plenty of soap and water.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.
- If eye irritation persists: Get medical advice/attention.
- In case of fire: Use Foam, Carbon Dioxide or Dry Chemical Powder for extinction.
- Store in a well-ventilated place. Keep cool.
- Store locked up.
- Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
- Dispose of contents/container in accordance with the relevant government legislation. Pressurised container; do not pierce or burn, even after use.

Fadeout Thinner Page 2 of 10

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Entity / Hazardous Component	CAS Numbers	Proportion by wt.
Dimethyl Ether	115-10-6	30 - 60%
Methoxy Propyl Acetate	108-65-6	10 - 30%
N-Butyl Acetate	123-86-4	10 - 30%
Xylene	1330-20-7	<10%
Dimethyl Glutarate	1119-40-0	<10%

4. FIRST AID MEASURES

Route of Exposure First Aid Measures

Ingestion: Give a glass of water. Do NOT induce vomiting. Place patients head

downwards if vomiting occurs. Prevent it entering lungs, as aspiration of material into the lungs can cause chemical pneumonitis which can be

fatal. Immediately call a POISON CENTER or doctor/physician.

Eye: Immediately irrigate with large quantities of water for at least 15 minutes.

Remove contact lenses, if present and easy to do so. Continue rinsing. If

eye irritation persists: Get medical advice/attention.

Skin: Wash exposed area thoroughly with soap and water. Remove

contaminated clothing. If skin irritation occurs: Get medical

advice/attention.

Inhaled: Give fresh air, careful not to become a casualty yourself. Remove and

loosen clothing. If breathing is normal make patient comfortable and keep warm till recovered. If breathing is difficult ensure the airways are clear and have a qualified person give oxygen from a face mask. If breathing has stopped commence (EAR) and if cardiac arrest has occurred,

commence (CPR) and get medical advice/attention urgently.

Advice To Doctor: Treat Symptomatically.

Fadeout Thinner Page 3 of 10

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media: Foam, Carbon Dioxide or Dry Chemical Powder.

Hazards from Combustion Products: If involved in a fire, toxic materials such as carbon monoxide, carbon dioxide, nitrogen oxide, isocyanate vapour, traces of hydrogen cyanide, hydrogen chloride gas, hydrogen fluoride gas, various chlorine and/or fluorine compounds as well as hydrocarbons may form.

Precautions for Firefighters: Flammable aerosol product. Pressurised container. Heating can cause rupture of containers with explosive force. If safe do so, remove all sources of ignition and any containers from the path of the fire. Keep cool with water spray.

Firefighters should wear self contained breathing apparatus with a full face and operated in the positive pressure mode.

Hazchem Code: 2[Y]

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions: In case of an accidental release or spill, evacuate the danger area. Wear the correct Personal Protective Equipment (See section 8 of SDS). Do not breathe vapours. Extinguish all ignition sources and shut off the source of the spill. Ventilate the area.

Environmental Precautions: Avoid release to the environment by bunding or covering drains.

Containment: Contain and absorb the spill with absorbent material such as sand, soil or vermiculite. Transfer the material into drums, using non-sparking tools. Seal and label the drums. Contact the appropriate waste management authority for disposal.

Fadeout Thinner Page 4 of 10

7. HANDLING AND STORAGE

Precautions For Safe Handling: Wear the correct Personal Protective Equipment (See Section 8 of the SDS) when using this product. Ground the container and receiving equipment whilst using. Only use non-sparking tools and take precautionary measures against static discharge.

Only use in a well-ventilated area or preferably apply the product in a spray paint booth with an adequate exhaust system and explosion-proof electrical, ventilation, and lighting equipment.

Never eat, drink or smoke whilst handling this product. Always wash hands thoroughly after using this product and before smoking, eating, drinking or using the toilet.

Conditions For Safe Storage: Keep containers away from heat/sparks/open flames/ hot surfaces. Store containers in a well-ventilated area and away sources of ignition, oxidising agents and/or foodstuffs. Store containers in a cool place (<50°C) and out of direct sunlight. Store containers away from bulk flammable materials, when not in use and check regularly for leaks. Store in accordance with AS3833-98 and local legislation.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits: TLV –TWA (mg/m³)

Dimethyl Ether 760

Methoxy Propyl Acetate 274

N-Butyl Acetate 713

Xylene 350

Dimethyl Glutarate Not Available

Engineering Controls: Ensure sufficient ventilation to maintain concentration below exposure standard. Only use in a well ventilated area or preferably apply the product in a spray paint booth with an adequate exhaust system. Keep containers sealed when not in use. Earth any mixing vessels when using this product.

Personal Protection: Skin contact should be avoided by wearing impervious work clothing, boots and Neoprene or PVC gloves. Eyes should be protected by chemical goggles or safety glasses fitted with side shields (Refer to AS/NZS 1337). If an inhalation risk exists, an organic vapour respirator or a self-contained breathing apparatus, with a full face and operated in the positive pressure mode, should be used. Ensure cartridges are correct for the potential air contamination (Refer to AS/NZS 1715 and 1716).

Fadeout Thinner Page 5 of 10

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Thin clear liquid.	
Odour:	Strong solvent odour.	
Odour Threshold:	Not Available	
pH:	Not Applicable.	
Melting Point/Freezing Point:	Not Applicable	
Boiling Point Range:	-25 – 225 ^o C	
Flash Point:	-41°C (Open Cup)	
Evaporation Rate:	0.007 - 1.00 (Butyl Acetate = 1)	
Flammability:	Extremely flammable aerosol.	
Flammability Limits:	1 (LEL) to 19% (UEL) by volume	
Vapour Pressure:	510 kPa @ 20°C	
Vapour Density:	Not Available	
Relative Density:	0.70 - 0.80	
Solubility In Water:	Not Available	
Partition Coefficient: n-octanol/water:	Not Available	
Auto-ignition Temperature:	354 ^o C	
Decomposition Temperature:	Not Available	
Viscosity:	10 – 12 seconds B4 Cup @ 25°C	

10. STABILITY AND REACTIVITY

Reactivity: No applicable information is available.

Chemical Stability: Stable under ordinary conditions of use and storage.

Conditions to Avoid: Avoid all ignition sources. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Incompatible Materials: None

Hazardous Decomposition Products: If involved in a fire, toxic materials such as carbon monoxide, carbon dioxide, nitrogen oxide, isocyanate vapour, traces of hydrogen cyanide, hydrogen chloride gas, hydrogen fluoride gas and various chlorine and fluorine compounds and hydrocarbons may form.

Hazardous Reactions: Not Applicable.

Fadeout Thinner Page 6 of 10

11. TOXICOLOGICAL INFORMATION

There is no data available on this product itself. The following information (where available) relates to the individual ingredients of the product.

Acute Toxicity – Oral:					
Ingredient Not Available	Value (LD50)	Species	GHS Category		
Health Effects:					
Acute:					
Chronic:					
Acute Toxicity – Dermal:					
Ingredient Not Available	Value (LD50)	Species	GHS Category		
Health Effects:					
Acute:					
Chronic:					
Acute Toxicity – Inhalation:					
Ingredient Not Available	Value (LC50)	Species	GHS Category		
Health Effects:					
Acute:					
Chronic:					
Skin Corrosion/Irritation: Not Available	GHS Category				
Health Effects:					
Acute:					
Chronic:					

Fadeout Thinner Page 7 of 10

Eye Damage/Irritation: GHS Category Methoxy Propyl Acetate 2A Health Effects: Causes serious eye irritation. Acute: Causes redness, tearing or blurred vision. Chronic: Will cause discomfort and may cause redness, itching or blurred vision. **Respiratory or Skin Sensitation: GHS Category** Not Available **Health Effects: Germ Cell Mutagenicity: GHS Category** Not Available **Health Effects: Carcinogenicity: GHS Category** Not Available **Health Effects: Toxic To Reproduction: GHS Category** Not Available **Health Effects: Specific Target Organ Toxicity (Single GHS Category** Exposure): Not Available **Health Effects: Specific Target Organ Toxicity (Repeated GHS Category** Exposure):

Aspiration HazardNot Available

GHS Category

Health Effects:

Not Available

Health Effects:

Fadeout Thinner Page 8 of 10

12.ECOLOGICAL INFORMATION

Environmental Precautions: Avoid release to the environment, the product should not be allowed to enter drains, water courses or the soil.

There is no data available on this product itself. The following information (where available) relates to the individual ingredients of the product.

Hazardous To The Aquatic Environment – Acute Hazard:

Ingredient Value (LC50) Species **GHS Category** Not Available **Effects: Hazardous To The Aquatic Environment – Long Term Hazard: GHS Category** Ingredient Value (LC50) Species Not Available Effects: **Exotoxic To Terrestrial Vertebrates:** Ingredient Value (LD50) Species **NZ Category** Not Available

Persistence and Degradability: No information available.

Bioaccumulative Potential: No information available.

Mobility in Soil: No information available.

Effects:

Fadeout Thinner Page 9 of 10

13. DISPOSAL CONSIDERATIONS

Contact the relevant waste management authority. Pressurised container; do not pierce or burn, even after use.

14. TRANSPORT INFORMATION

ADG (Land): NZS 5433:

Shipping Name: AEROSOLS - FLAMMABLE Shipping Name: AEROSOLS - FLAMMABLE

UN Number: 1950 UN Number: 1950 Hazard Class: 2.1 Hazard Class: 2.1

Subsidiary Risk: Not Applicable Subsidiary Risk: Not Applicable Packaging Group Not Applicable Packaging Group Not Applicable

Hazchem 2[Y] Hazchem 2[Y]

IMGD (Sea): ICAO/IATA (Air):

Shipping Name: AEROSOLS - FLAMMABLE Shipping Name: AEROSOLS - FLAMMABLE

UN Number: 1950 UN Number: 1950 Hazard Class: 2.1 Hazard Class: 2.1

Subsidiary Risk: Not Applicable Subsidiary Risk: Not Applicable Packaging Group: Not Applicable Packaging Group Not Applicable

Packaging Group: Not Applicable Packaging Group Not Applicable Marine Pollutant: No F-D,S-U

15. REGULATORY INFORMATION

Poisons Schedule: Not Scheduled

HSNO Group Standard: HSR002515 - Aerosols (Flammable)

16. OTHER INFORMATION

Date of Issue: 20/09/19 Replaces Issue Dated:

The above information has been presented in good faith and is accurate to the best of our knowledge, at the time of preparation. All of the information supplied herein is related only to the health and safety issues of the product. Users should assume all responsibility for its use, as the conditions under which this product is used are beyond our control. For technical information on the use of this product users should consult the appropriate Technical Data Sheet.

END OF SDS

Fadeout Thinner Page 10 of 10