

Date: 21st October 2016

Technical Data Sheet

Version: 01

Product Name			
Full Product Name	Graffiti Remover (Aerosol)		
Type of Product	1K graffiti remover		
Description	Concept Graffiti Remover (Aerosol) is an environmentally friendly formula suitable for the removal of all types of graffiti. Although it has been designed to remove graffiti from most surfaces, care should be taken when removing graffiti applied to an existing painted surface, as it may damage the existing painted surface.		

Properties

- · Environmentally friendly
- Suitable for most surfaces
- · Effectively removes unwanted paint
- Ready for use (aerosol)

Substrates

- Glass
- Brick
- Concrete
- Metal
- Existing finishes such as Colourbond (always check first)

Substrate Preparation Mask off any surrounding areas using a polyethylene plastic sheet or aluminium foil to avoid overspray and protect areas not affected by graffiti.



Date: 21st October 2016

Technical Data Sheet

Version: 01

Product Preparation

	Shake can	Invert and shake the can thoroughly, until the agitation ball can be heard (two to three minutes). Continue to shake the can during application.		
A B	Pot life @ 25°C (77°F)	N/A		
S	Spray viscosity @ 25°C (77°F)	BSB 4 Cup Ford 4 Cup		
	Application	 Apply one even coat directly to the graffiti. Wait approximately 3 to 5 minutes. Rinse area clean with water. 		
Number of		1	Apply one even coat directly to the graffiti.	
	coats	Notes:	 Depending on the type of graffiti being removed, multiple applications may be necessary Masonry walls or aged graffiti may require scrubbing with a soft natural bristle brush 	
	DFT Recommended	25 μm 1.0 mil		
<u> </u>	Flash off time @ 25°C (77°F)	3-5 min		
	Drying	Air Dry @ 25°C (77°F) N/A		

This data relates only to the material designated herein and does not apply to use in combination with any other material or any process. The data is not to be considered as a warranty or quality specification and we assume no liability in connection with its use.

Remarks	
● F / °C	Surface temperature must always be a minimum of 3°C (5°F) above dew point.

Equipment Cleaning	
	Turn the can upside down and spray until the jet clears.



Date: 21st October 2016

Technical Data Sheet

Version: 01

Dry Film Properties	when compared to similar technology products.	
Removal of Graffiti	Excellent	
Residue remaining	Nil	

Product Data		
Colour	Clear	
Theoretical Coverage	Approx. 2.0 m ² (80 ft ²)/426g @ recommended DFT	
Shelf Life	36 months in an unopened container at room temperature away from sunlight.	

Product Packaging			
Product Code 1	Product Code 2	Product Name	Package Size
A02C/STRIP		Graffiti Remover (Aerosol)	426g (aerosol)

Safety

Before using, read and follow all label and Safety Data Sheet (SDS) precautions, including respiratory protection and other Personal Protective Equipment such as safety clothing, glasses and gloves. Use only in a well-ventilated area.

The information provided in this documentation has been carefully selected and arranged by us. It is based upon our best knowledge on the subject at the date of issuance. The Information is given for information purposes only. We are not liable for its correctness, accuracy and completeness. It is up to the user to check if the information is current and the product is suitable for its intended purpose. The intellectual property in this Information, including patents, trademarks and copyrights, is protected. All rights reserved.

We may modify and/ or discontinue operation of all or portions of this Information at any time in our sole discretion, without notice and assume no responsibility to update the Information. All rules set forth in this clause shall apply accordingly for any future changes and amendments.

This Technical Data Sheet supersedes all previous issues.

Concept Paints 26-30 Charles Street St Marys NSW 2760 Sydney, Australia ph. +61 (2) 9673 2555 fax. +61 (2) 9623 1918 info@conceptpaints.com.au www.conceptpaints.com.au