

SAFETY DATA SHEET

1. IDENTIFICATION

PRODUCT(S): ACRYLIC BLACK SPRAYPAK

Supplier In Australia: Concept Paints

Address: 26 - 30 Charles Street, St Marys, Australia. 2760

Telephone Number: +61 2 96732555

Emergency Telephone: +61 2 96732555 (Monday to Friday 8am to 5pm)

Supplier In NZ: GPI Automotive (NZ) Ltd

Address: 59 Greenmount Drive, East Tamaki, Auckland, New Zealand

Telephone Number: +64 9 274 4943

Emergency Telephone: +64 9 274 4943 (Monday to Friday 8am to 5pm)

Recommended Use: Aerosol for Industrial and Commercial Use

2. HAZARDS IDENTIFICATION

Classification:

- HAZARDOUS SUBSTANCE.
- DANGEROUS GOODS. (According to the criteria of ADG Code and NZ 5433.)

CLASSIFICATION	GHS CATEGORY	NZ CATEGORY	SIGNAL WORD	HAZARD STATEMENT
Flammable Aerosols	1	2.1.2A	Danger	Extremely flammable aerosol.
Skin Corrosion/ Irritation	3	6.3B	Warning	Causes mild skin irritation.
Eye Damage/ Irritation	2A	6.4A	Warning	Causes serious eye irritation.
Toxic To Reproduction	1	6.8A	Danger	May damage fertility or the unborn child.

Hazard Symbols:







Precautionary Statements:

- Obtain special instructions for use.
- Do not handle until all safety precautions have been read and understood.
- Keep away from heat/sparks/open flames/ hot surfaces. No smoking.
- Do not spray on an open flame or other ignition source.
- · Keep container tightly closed.
- Ground/bond container and receiving equipment.
- Use explosion-proof electrical/ventilation/lighting/equipment.
- Use only non-sparking tools.
- Take precautionary measures against static discharge.
- Pressurised container; do not pierce or burn, even after use.
- · Wash hands thoroughly after handling.
- Wear protective gloves/protective clothing/eye protection/face protection.
- IF ON SKIN (or hair): Remove /take off immediately all contaminated clothing. Wash skin with plenty of soap and water.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.
- IF exposed or concerned: Get medical advice/attention.
- If skin irritation occurs: Get medical advice/attention.
- If eye irritation persists: Get medical advice/attention.
- Take off contaminated clothing and wash before reuse.
- In case of fire: Use Foam, Carbon Dioxide or Dry Chemical Powder for extinction.
- Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
- Store in a well-ventilated place. Keep cool.
- Store locked up.
- Dispose of contents/container in accordance with the relevant government legislation. Pressurised container; do not pierce or burn, even after use.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Entity / Hazardous Component	CAS Numbers	Proportion by wt.
Dimethyl Ether	115-10-6	30 - 60%
Xylene	1330-20-7	10 - 20%
Acetone	67-64-1	10 - 20%
Toluene	108-88-3	<10%
N-Butyl Acetate	123-86-4	<10%
Methoxy Propyl Acetate	108-65-6	<10%
Benzyl Butyl Phthalate	85-68-7	<10%
Iso-Butanol	78-83-1	<5%

This product(s) also contains 10 – 30% of other ingredients which are considered non-hazardous in accordance with ASCC/NOHSC and NZ HSNO criteria.

4. FIRST AID MEASURES

Route of Exposure First Aid Measures

Ingestion: Give a glass of water. Do NOT induce vomiting. Place patients head

downwards if vomiting occurs. Prevent it entering lungs, as aspiration of material into the lungs can cause chemical pneumonitis which can be

fatal. Immediately call a POISON CENTER or doctor/physician.

Eye: Immediately irrigate with large quantities of water for at least 15 minutes.

Remove contact lenses, if present and easy to do so. Continue rinsing. If

eye irritation persists: Get medical advice/attention.

Skin: Wash exposed area thoroughly with soap and water. Remove

contaminated clothing. If skin irritation occurs: Get medical

advice/attention.

Inhaled: Give fresh air, careful not to become a casualty yourself. Remove and

loosen clothing. If breathing is normal make patient comfortable and keep warm till recovered. If breathing is difficult ensure the airways are clear and have a qualified person give oxygen from a face mask. If breathing has stopped commence (EAR) and if cardiac arrest has occurred,

commence (CPR) and get medical advice/attention urgently.

Advice To Doctor: Treat Symptomatically.

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media: Foam, Carbon Dioxide or Dry Chemical Powder.

Hazards from Combustion Products: If involved in a fire, toxic materials such as carbon monoxide, carbon dioxide, nitrogen oxide, isocyanate vapour, traces of hydrogen cyanide, hydrogen chloride gas, hydrogen fluoride gas, various chlorine and/or fluorine compounds as well as hydrocarbons may form.

Precautions for Firefighters: Flammable aerosol product. Pressurised container. Heating can cause rupture of containers with explosive force. If safe do so, remove all sources of ignition and any containers from the path of the fire. Keep cool with water spray.

Firefighters should wear self contained breathing apparatus with a full face and operated in the positive pressure mode.

Hazchem Code: 2[Y]

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions: In case of an accidental release or spill, evacuate the danger area. Wear the correct Personal Protective Equipment (See section 8 of SDS). Do not breathe vapours. Extinguish all ignition sources and shut off the source of the spill. Ventilate the area.

Environmental Precautions: Avoid release to the environment by bunding or covering drains.

Containment: If an aerosol can develops a leak, allow it to fully discharge, before disposal. Contain and absorb any spill with absorbent material such as sand, soil or vermiculite. Transfer the material into drums, using non-sparking tools. Seal and label the drums. Contact the appropriate waste management authority for disposal.

7. HANDLING AND STORAGE

Precautions For Safe Handling: Wear the correct Personal Protective Equipment (See Section 8 of the SDS) when using this product. Ground the container and receiving equipment whilst using. Only use non-sparking tools and take precautionary measures against static discharge.

Only use in a well-ventilated area or preferably apply the product in a spray paint booth with an adequate exhaust system and explosion-proof electrical, ventilation, and lighting equipment.

Never eat, drink or smoke whilst handling this product. Always wash hands thoroughly after using this product and before smoking, eating, drinking or using the toilet.

Conditions For Safe Storage: Keep containers away from heat/sparks/open flames/ hot surfaces. Store containers in a well-ventilated area and away sources of ignition, oxidising agents and/or foodstuffs. Store containers in a cool place (<50°C) and out of direct sunlight. Store containers away from bulk flammable materials, when not in use and check regularly for leaks. Store in accordance with AS3833-98 and local legislation.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits:	TLV –TWA (mg/m ³)
Dimethyl Ether	760
Xylene	350
Acetone	1185
Toluene	191
N-Butyl Acetate	713
Methoxy Propyl Acetate	274
Benzyl Butyl Phthalate	Not Available
Iso-Butanol	152

Engineering Controls: Ensure sufficient ventilation to maintain concentration below exposure standard. Only use in a well ventilated area or preferably apply the product in a spray paint booth with an adequate exhaust system. Keep containers sealed when not in use. Earth any mixing vessels when using this product.

Personal Protection: Skin contact should be avoided by wearing impervious work clothing, boots and Neoprene or PVC gloves. Eyes should be protected by chemical goggles or safety glasses fitted with side shields (Refer to AS/NZS 1337). If an inhalation risk exists, an organic vapour respirator or a self-contained breathing apparatus, with a full face and operated in the positive pressure mode, should be used. Ensure cartridges are correct for the potential air contamination (Refer to AS/NZS 1715 and 1716).

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Thin black liquid.
Odour:	Strong solvent odour.
Odour Threshold:	Not Available
pH:	Not Applicable.
Melting Point/Freezing Point:	Not Applicable
Boiling Point Range:	-25 – 145 ^o C
Flash Point:	-41 ^o C (Open Cup)
Evaporation Rate:	0.40 - 10.00 (Butyl Acetate = 1)
Flammability:	Extremely flammable aerosol.
Flammability Limits:	1 (LEL) to 19% (UEL) by volume
Vapour Pressure:	510 kPa @ 20 ^o C
Vapour Density:	Not Available
Relative Density:	0.80 - 0.90
Solubility In Water:	Not Available
Partition Coefficient: n-octanol/water:	Not Available
Auto-ignition Temperature:	354 ^o C
Decomposition Temperature:	Not Available
Viscosity:	14 – 18 seconds B4 Cup @ 25°C

10. STABILITY AND REACTIVITY

Reactivity: No applicable information is available.

Chemical Stability: Stable under ordinary conditions of use and storage.

Conditions to Avoid: Avoid all ignition sources. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Incompatible Materials: None

Hazardous Decomposition Products: If involved in a fire, toxic materials such as carbon monoxide, carbon dioxide, nitrogen oxide, isocyanate vapour, traces of hydrogen cyanide, hydrogen chloride gas, hydrogen fluoride gas and various chlorine and fluorine compounds and hydrocarbons may form.

Hazardous Reactions: Not Applicable.

11. TOXICOLOGICAL INFORMATION

There is no data available on this product itself. The following information (where available) relates to the individual ingredients of the product.

Acute Toxicity – Oral:			
Ingredient Not Available	Value (LD50)	Species	GHS Category
Health Effects:			
Acute:			
Chronic:			
Acute Toxicity – Dermal:			
Ingredient Not Available	Value (LD50)	Species	GHS Category
Health Effects:			
Acute:			
Chronic:			
Acute Toxicity – Inhalation:			
Ingredient Not Available	Value (LC50)	Species	GHS Category
Health Effects:			
Acute:			
Chronic:			
Skin Corrosion/Irritation: Acetone	GHS Category 3		
Health Effects: Causes mild skin irritation.			
Acute: Causes mild skin irritation.			

Chronic: May cause dermatitis and eczema.

Eye Damage/Irritation: Acetone	GHS Category 2A		
Health Effects: Causes serious eye irritation.			
Acute: Causes redness, tearing or blurred vision.			
Chronic: Will cause discomfort and may cause red	dness, itching or blurred vision.		
Respiratory or Skin Sensitation: Not Available	GHS Category		
Health Effects:			
Germ Cell Mutagenicity: Not Available	GHS Category		
Health Effects:			
Carcinogenicity: Not Available	GHS Category		
Health Effects:			
Toxic To Reproduction: Benzyl Butyl Phthalate Toluene	GHS Category 1 1		
Health Effects: May damage fertility or the unbor	n child.		
Specific Target Organ Toxicity (Single Exposure): Not Available	GHS Category		
Health Effects:			
Specific Target Organ Toxicity (Repeated Exposure): Not Available	GHS Category		
Health Effects:			
Aspiration Hazard Not Available	GHS Category		
Health Effects:			

12.ECOLOGICAL INFORMATION

Environmental Precautions: Avoid release to the environment, the product should not be allowed to enter drains, water courses or the soil.

There is no data available on this product itself. The following information (where available) relates to the individual ingredients of the product.

Hazardous To The Aquatic Environment – Acute Hazard:

Ingredient Not Available	Value (LC50)	Species	GHS Category
Effects:			
Hazardous To The Aquatic Environment – L	ong Term Hazard:		
Ingredient Not Available	Value (LC50)	Species	GHS Category
Effects:			
Exotoxic To Terrestrial Vertebrates:			
Ingredient Not Available	Value (LD50)	Species	NZ Category
Effects:			

Persistence and Degradability: No information available.

Bioaccumulative Potential: No information available.

Mobility in Soil: No information available.

13. DISPOSAL CONSIDERATIONS

Contact the relevant waste management authority. Pressurised container; do not pierce or burn, even after use.

14. TRANSPORT INFORMATION

ADG (Land): NZS 5433:

Shipping Name: AEROSOLS - FLAMMABLE Shipping Name: AEROSOLS - FLAMMABLE

UN Number: 1950 UN Number: 1950 Hazard Class: 2.1 Hazard Class: 2.1

Subsidiary Risk: Not Applicable Subsidiary Risk: Not Applicable Packaging Group Not Applicable Packaging Group Not Applicable

Hazchem 2[Y] Hazchem 2[Y]

IMGD (Sea): ICAO/IATA (Air):

Shipping Name: AEROSOLS - FLAMMABLE Shipping Name: AEROSOLS - FLAMMABLE

UN Number: 1950 UN Number: 1950 Hazard Class: 2.1 Hazard Class: 2.1

Subsidiary Risk: Not Applicable Subsidiary Risk: Not Applicable

Packaging Group: Not Applicable Packaging Group Not Applicable Marine Pollutant: No F-D,S-U

15. REGULATORY INFORMATION

Poisons Schedule: Not Scheduled

HSNO Group Standard: HSR002515 - Aerosols (Flammable)

16. OTHER INFORMATION

Date of Issue: 31/08/16

Replaces Issue Dated: 27/07/15

The above information has been presented in good faith and is accurate to the best of our knowledge, at the time of preparation. All of the information supplied herein is related only to the health and safety issues of the product. Users should assume all responsibility for its use, as the conditions under which this product is used are beyond our control. For technical information on the use of this product users should consult the appropriate Technical Data Sheet.

END OF SDS