










Product Name	
Full Product Name	Wax & Grease Remover Aerosol
Type of Product	1K surface cleaner
Description	Concept Wax & Grease Remover Aerosol is a solvent based cleaner for the removal of surface contaminants prior to painting. It can be used for cleaning any paint or metal surface.

Properties	
<ul style="list-style-type: none">• Suitable for most surfaces without damaging existing sound paintwork	
<ul style="list-style-type: none">• Effective cleaner	
<ul style="list-style-type: none">• Ready for use (aerosol)	


Substrates	
<ul style="list-style-type: none">• Metal surfaces	
<ul style="list-style-type: none">• Existing finishes in sound condition	

Substrate Preparation	
 All Substrates	N/A


Product Preparation

	Shake can	Invert and shake the can thoroughly, until the agitation ball can be heard (two to three minutes). Continue to shake the can during application.	
	Pot life @ 25°C (77°F)	N/A	
	Spray viscosity @ 25°C (77°F)	BSB 4 Cup Ford 4 Cup	N/A
	Application	<ul style="list-style-type: none"> • Spray the area to be cleaned in an even overlapping pattern from a distance of approximately 25 centimetres. Wipe the area with a clean cloth before the cleaner evaporates, to remove any contamination. • To remove severe contamination, repeat cleaning, always wiping with a clean cloth, until the area is free from all contamination. 	
	Number of coats	N/A	
	DFT Recommended	N/A	
	Flash off time @ 25°C (77°F)	0 min (no flash-off required)	
	Drying	Air Dry @ 25°C (77°F)	N/A
<p>This data relates only to the material designated herein and does not apply to use in combination with any other material or any process. The data is not to be considered as a warranty or quality specification and we assume no liability in connection with its use.</p>			

Remarks

	Surface temperature must always be a minimum of 3°C (5°F) above dew point.
---	--

Equipment Cleaning

	Turn the can upside down and spray until the jet clears.
---	--

Dry Film Properties

After 7 days drying,
when compared to similar technology products.

Not Applicable

Product Data

Colour	Clear
Theoretical Coverage	N/A
Shelf Life	36 months in an unopened container at room temperature away from sunlight.

Product Packaging

Product Code	Product Name	Package Size
AU0369000.400	Wax & Grease Remover Aerosol	400g (aerosol)

Safety

Before using, read and follow all label and Safety Data Sheet (SDS) precautions, including respiratory protection and other Personal Protective Equipment such as safety clothing, glasses and gloves. Use only in a well-ventilated area.

The information provided in this documentation has been carefully selected and arranged by us. It is based upon our best knowledge on the subject at the date of issuance. The Information is given for information purposes only. We are not liable for its correctness, accuracy and completeness. It is up to the user to check if the information is current and the product is suitable for its intended purpose. The intellectual property in this Information, including patents, trademarks and copyrights, is protected. All rights reserved.

We may modify and/ or discontinue operation of all or portions of this Information at any time in our sole discretion, without notice and assume no responsibility to update the Information. All rules set forth in this clause shall apply accordingly for any future changes and amendments.

This Technical Data Sheet supersedes all previous issues.

Concept Paints
26-30 Charles Street
St Marys NSW 2760
Sydney, Australia

ph. +61 (2) 9673 2555
fax. +61 (2) 9623 1918
office@conceptpaints.com.au
www.conceptpaints.com.au